LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF-:	LOCATED IN-:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. S., R. 6 E. W.	A-8;
2. PROPERTY CONTROLLING IN SECTION 19	T. 19 N. S., R. 6 E. W.	12; 9
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 13, 19 85, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

~~A. Description of original monument and accessories used on subsequent restoration:~~

A-8

Fd 1¼"x 4' galv pipe & 3 clay tiles;
added DNR mon & cedar post

21" Oak	N45°W	6.15'
14" Oak	N10°E	27.88'
15" Oak	S50°E	20.33'
11" Oak	S50°W	51.34'
Ctr winding trail N-S	West	18'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

A-8 - Fd 1¼' pipe & 3 Clay tiles; remains of U.S.B.T. stump N.W. Fits Schaaf N.B.T. remains. Schaaf notes (Dec. 1939) indicate he had U.S.B.T. stump NW. Corner is in line with old W-W fn to west, in trees.

12 - Established SW corner of NW¼ of frl. SE¼ of Sec. 19 per prorated (on acreage basis) to G.L.O. plat, 1856-1857 dependent resurvey (run-out on S¼ mile of Sec. 19).

9 - Established SW corner of SE¼ of NE¼ of Sec. 19; equidistant & on line between the center & E¼ Cor. of Section 13.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

12

Drove 5/8"x 34" re-rod w/RLS cap,
set cedar post w/loc tag

6" Red Pine	N55°E	32.7'
4" Twin Red Pine	Due S	14.1'
13" Black Oak	S35°W	31.3'
Ctr N-S dirt rd	Due W	64'

9

Drove 5/8"x34" re-rod w/RLS cap &
set cedar post w/Loc. tag

12" Black Oak	N55°E	13.2'
9" Black Oak	N25°W	33.6'
13" Black Oak	S80°W	7.5'
Ctr trail	Due E	165'

SIGNED BY Carl F. Roser 01-06-86 DATE

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

REDDING TWP
CLARE COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

Reproduced by the Sec of State of Michigan