

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>19</u> N. <u>6</u> W.	<u>E-9</u> ;
2. PROPERTY CONTROLLING IN SECTION <u>20</u>	T. <u>19</u> N. <u>6</u> W.	<u>15</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 6, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-9 - Fd 1½" pipe (Schaaf pipe) with RLS cap in plug in pipe (G. DeLaMater); pipe is 18" out of ground. Fits Schaaf wits. whose notes (Aug. 1939) indicate he had original corner here (1856 dependent resurvey).

15 - Found old 1½" pipe for SW Cor. of SE¼ of SW¼ of Section 20. Fits Aug., 1939 B.T.'s by Marcus Schaaf.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>E-9</u>		<u>15</u>
Fd 1½" pipe w/RLS cap; added squared cedar post		Fd old 1½" pipe; added cedar post w/loc tag
13" Maple S50°W 15.16'		16" Oak N85°W 36.75'
11" Maple N10°W 47.29'		3" White Pine N10°W 4.63'
8" Black Oak N75°W 36.97'		12" Oak S65°E 12.68'
3" Black Oak S60°E 21.60'		


SIGNED BY Carl F. Roser 01-06-86 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)



SURVEYOR'S MICHIGAN REGISTRATION NO. _____
REDDING TWP
CLARE COUNTY

Approved by the State of Michigan