# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF—: | LOCATED IN—: | CORNER CODE NUMBER |
|---|---|---|
| 1. PUBLIC LAND SURVEY | T. 19 N. ●., R. 6 ●. W. | G-8; H-8; |
| 2. PROPERTY CONTROLLING IN SECTION 22 | ,T. 19 N. ●., R. 6 ●. W. | 14 |
| 3. MISCELLANEOUS PROPERTY IN SECTION | ,T. N. S., R. E. W. | |
| 4. LOT NO. , RECORDED PLAT | | |
| 5. PRIVATE CLAIMS | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 25, 19 85, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

G-8

Drove 5/8" x 34" re-rod w/RLS cap flush

| | | |
|---|---|---|
| 8" Red Pine | S60°W | 55.70' |
| 22" Red Pine | N55°W | 70.52' |
| Ctr N-S bit. rd | Due E | 7' |
| Set ced post w/loc tag | West | 33' |

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G-8 - Re-establish W¼ Cor. of Sec. 22 mid-way & on line between NW & SW Cor's of Sec. 22. Old fn. remains (on ground) to west are 30'± north. Fn to east is 12'± north.

H-8 - Established ctr. of Sec. 22 at intersection of one-quarter lines. Fd ½" re-rod, S00°32'W, 3.45'

14 - Established Se Corner of NE¼ of SE¼ of Sec. 22 per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-8

Set 5/8"x 34" re-rod w/RLS cap & cedar post w/loc tag

| | | |
|---|---|---|
| 24" Black Oak | N35°W | 12.5' |
| 4" Black Oak | S15°E | 28.1' |
| 3" Black Oak | S80°W | 14.4' |
| RR Row fn | Due N | 3' |
| Fd 1¼" pipe | S19°21'W | 24.85' |
| Ctr R.R. tracks | Due S | 60' |

14

Set 5/8"x 34" re-rod w/RLS cap & cedar post w/loc tag

| | | |
|---|---|---|
| 4" Black Oak | N60°W | 22.9' |
| 25" White Oak | N70°E | 65.9' |
| 16" Basswood | Due E | 81.8' |
| Cor of fn N'ly & RR Row fn | S85°E | 31' |
| Ctr RR tracks | Due S | 40' |

SIGNED BY Carl F. Roser 01-06-86 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

REDDING TWP
CLARE COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

Reproduced by the Surveyor of Michigan