

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: _____ Located In _____ Corner Code # _____
 Clare (County)

1. Public Land Survey
 T _____ R _____
 T _____ R _____
2. Property Controlling in Section
 S 5 T 20N R 3W 12
 S 5 T 20N R 3W 13
3. Miscellaneous Property in Section
 S _____ T _____ R _____
 S _____ T _____ R _____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on Sept. 9, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3		●	●									
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

Register of Deeds Stamp & File Number

A. Description of original monument and accessories and/or subsequent restoration:

12 - None 13 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

12- CS 1/16 Corner Sec. 5 13 - SE 1/16 Corner Sec. 5
 Set 2" Alum. cap on 5/8" X 3/4" rebar per standard BLM procedure. CL. of N-S Gravel Rd. is 75± E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
12 - Stamped 2" Alum. Cap on 5/8" x 3/4" iron rebar
 Set Blue Carsonite Post 1' NE
 S14°E 28.93' to set N&T in E side c/p. 12" R. Maple
 S68°E 27.38' to set N&T in S side twin 8" R. Maple
 N12°E 22.75' to set N&T in W side 6" R. Maple
 N64°W 26.30' to set N&T in S side triple 10" R. Maple

13 - Stamped 2" Alum. Cap on 5/8" x 3/4" iron rebar
 Set Blue Carsonite Post with location tag 1' NE
 N60°E 11.53' to set N&T in SE side 1 1/2" R. Maple
 S68°E 22.46' to set N&T in N side tn 10" R. Maple
 N26°W 31.16' to set N&T in NE side 8" Oak
 S62°W 35.30' to set N&T in SE side 14" R. Maple

Signed by: Craig W. McVean Date: 12/3/2003
 Surveyor's Michigan License No.: 39088