

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>20</u> N. <u>6</u> R. <u>6</u> W. <u>●</u>		K-4; K-5; K-6; K 7
2. PROPERTY CONTROLLING IN SECTION _____ T. _____ N. _____ S. _____ R. _____ E. _____ W. _____		
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ S. _____ R. _____ E. _____ W. _____		
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 3, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monument and accessories and/or subsequent restoration:~~

C. (continued)

K-7
Set DNR monument at 1/2" bar
5" J. Pine N43°E 42.05
5" R. Pine S33°E 38.05


B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K-4 Found large rock, glass and can of charcoal at corner, probably set in early county survey.
- K-5 Found 3/4" pipe, previously located and witnessed by Consumers Power Company.
- K-6 Found 1-3/4" iron bar in N-S trail road, probably set in early county surveyor's survey.
- K-7 Found 1/2" bar over old 1 1/4" pipe apparently used in other surveys.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-4	K-5	K-6
Set 1"x36" iron pipe & cedar post	Set DNR mon. & red-top post	Left 1-3/4" iron bar in place
5" Maple S30°E 46.6	9" W. Oak N40°E 15.9	set cedar post
8" W. Oak S88°W 47.3	8" R. Oak S23°E 19.1	4" J. Pine S40°E 11.7
1" Balsam N32°E 13.3		5" J. Pine S83°E 43.95

SIGNED BY *Kenneth J. Ostling* DATE June 18, 1976
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CLARE COUNTY