Remonumentation

MAY 1 7 1995

Signed by

Surveyor's Michigan License No.

Santonanian

Bingham A-1 / Bengal M-1 / Essex M-13 / Greenbush A-13

COMMISSION		·	LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970					RECORDED									
For corners	in							LIB	ER	<u>4, I</u>	AGE	6	<u>4</u>	1.			
Clinton			ited In:	Corner	Code ##		₽		ay	2	$2^{\frac{1}{2}}$	 n D			,		
1. Public Land Survey T 7N R 2W A - 1 T R T R T R T R T R T R T R T R T R T							CLINTON COUNTY, MIGH.										
2. Property	/ Controlling		R														
in Secti	on	S T _	R		·				•								
3. Miscellaneous S T R F									eds	Star	np & l	File I	Nun	nber			
Property	y in Sec.	S T _	R	·													
							<u>.</u>	B (; D	E	F G	H I	IJ	K	L		
5. Private	Claims		 		· · · · · · · · · · · · · · · · · · ·	;	,	ŢŢ	Ţ	T		\Box		T	Ţ		
						•	3	i	- 5- 	Τ.		·1	_		-1-		
							,	1-1	\top	_				寸	_		
			_		•	•	一	<u>} </u>	— 8-	 - -	9—	-10	-1	'十	12- 		
					. 19 <u>94</u> , 19 <u>94</u> ,		⁵├─	$\vdash \vdash$		╫	-	+-1		-	+		
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the								8	—1'7—	╌┼╌	6	-15	1	Ч	-13-		
current manual of survey instructions of the United States Department of the Interior, Bureau of Land								╂╼╌╂			-	-					
•	,			•	oned in lines 3, 4 and 5		3	9	— 20-	2	1——	-22	2	<u>-</u>	24-		
					ors or by a Decree of a recovered, found as		-		_{			4					
expressed be	•	ro coldonomou, 1				10	هـــاد	 	29-	2	8	-27	2	-	25-		
NOTE: No	t more than 4 o	corners, all in th	ne same town	and range, ma	v be recorded	11	بل.			┺							
	this certificate				•	12	2	<u>.</u>	_32-	1.	3	-34	_3	<u>.</u>	_36-		
						13	3		Ĩ						Ï		
Original sur No county s Subsequen at centerline N 5 S 6 S 6 S 4 B. Descrip Found RR 3	vey by Chas of surveyor record to recordation of corner of Spike 0.80' be	of this corner by with the following 18.60' 15.75' 16.20' 15.00' evidence found low gravel surf	ebruary of 183 y Mark VanRa ng witnesses; South edge r top center tel N & T #1137 N & T #1137 (\$ and/or method face	eemdonck reco road sign post lephone cable 0 SW face cut 0 in W face w SEE BACK O	orded in L.2, P.733 box t-off U/P cod post F SHEET) storing or reestablist	,			stal	ling	he fo	und	a R	R S	pike		
		8.60'		oad sign post			•										
S 6 and is acce	0° E 5 pled as the be	6.20'	N & T #1137 Idence of the	lephone cable 0 SW face cul position of the r Recordation	t-off U/P e original corner. R	lemove	ed R	R S	pike	anc	set :	stano	dan	d CI	into		
												ROVEI					
		CLINTON COUNTY PEER GROUP DATED 12/7/94															
		230															
									•		C	, , _	- 1				
					·												
C. Descrip	tion of monume	ent for comer a	nd accessories	s established to	o perpetuate locatin	ig the p	osit	ion (of the	e co	rner:						
	N S S	60° E 4.68 84	38.60' 55.75' 56.20' ***	top center N & T #113	e road sign post GTE riser box 370 SW face cut o	ff Utilli	ity !	Pole	•			·					

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 197: REVISED MAY 14, 197! REVISED JAN., 1981

December 21, 1994

LIBER 4, PAGE 65

Field Notes from James Porter dated 6/11/90 indicates he found a RR Spike at this location

Unrecorded survey by Mark VanRaemdonck and an unrecorded survey by Dwight Schofield both reference this corner.