

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 25 N. R. 3 W.	K-3; L-3
2. PROPERTY CONTROLLING IN SECTION 1	T. 25 N. R. 3 W.	15
3. MISCELLANEOUS PROPERTY IN SECTION 1	T. 25 N. R. 3 W.	11-15
4. LOT NO. _____	RECORDED PLAT _____	
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 9, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on April 9, 1979, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. - Description of original monument and accessories and/or subsequent restoration:

C. (continued)

11-15
 Set 5/8" rod w/RLS Cap
 3" J. Pine S64°E 10.35
 4" J. Pine S01°E 27.86
 3/4" Rod S14½°W 4.15

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- K-3 (A) RR rail probably set by Newman, first found by Henning 1955.
- (B) Corner in place as found & rewitnessed in 1969 DNR survey; rewitnessed now for proper recording.
- L-3 Found ½" iron bar in place as established in 1960 survey by O.S.I. of Sec. 12. Rewitnessed for proper recording at this time.
- 15 Set corner by standard survey procedure for the subdivision of sections.
- 11-15 Set property corner by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3	L-3	15
Found RR Rail	Fd. ½" rod, set DNR mon. & cedar Post	Set 5/8" rod w/RLS Cap
9" J. Pine (1969) S69°W 64.3	5" J. Pine N57°W 29.91	5" J. Pine N32°W 11.1
8" J. Pine (1969) S61°E 82.0	14" Tw. R. Pine N32°E 63.87	3" J. Pine N79°W 12.07
12" J. Pine (1969) N51°E 86.87		
Cedar Post West 34		

SIGNED BY

Kenneth J. Ostling

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CRAWFORD COUNTY