LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T S., R	E	
2. PROPERTY CONTROLL- 12 ING IN SECTION	_ ,T. <u>25</u> ^{N.} , R. <u>4</u>	11 ; 15	
3. MISCELLANEOUS PROPERTY IN SECTION	,T	E.	
4. LOT NO , REC	ORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in l re-established, monumented, re- and rules therefore as required a Bureau of Land Management or and 5 above were, in a field surv	ines I and 2 above were, monumented, recovered in the current manual of by a decree of a court of ey on	eby certify that under requirements in a field survey on May 10 or restored as expressed below an survey instructions of the United f law. Furthermore, that the corner, 19, found, recovered, rethe Michigan State Board of Regis	d in conformance with regulation States Department of the Interior er points mentioned in lines 3, stored, established or re-establish
A. Description of original monu	ment and accessories and	I/or subsequent restoration:	
-		applied in restoring or re-establishing	
Set by standard surv	ey procedure for	applied in restoring or re-establishing the subdivision of sections are for the subdivision of	ons.
Set by standard surv	vey procedure for	the subdivision of secti	ons. f sections.
Set by standard survice Corner set by standard Corner set by standard Corner set by standard Corner set by standard Survice	rey procedure for	the subdivision of sections of the subdivision of t	ons. f sections.
Set by standard survice Corner	rey procedure for and survey procedure reorner and accessories and the survey procedure for a corner and accessories and the survey sq. rod the survey procedure.	the subdivision of section of the subdivision of the subdivision of the subdivision of the stablished to perpetuate locating the section of t	ons. f sections. he position of the corner: . rod &
Corner set by standard	rey procedure for and survey procedure recorner and accessories of the sq. rod & post	the subdivision of sections of the subdivision of the subdivision of the subdivision of the stablished to perpetuate locating the section of the subdivision of the s	ons. f sections. he position of the corner: rod &
Corner set by standard	rey procedure for and survey procedure recorner and accessories and the survey procedure recorner and accessories and the survey sq. rod the surve	the subdivision of section of the subdivision of the subdivision of the subdivision of the stablished to perpetuate locating the section of the subdivision of the su	ons. f sections. he position of the corner: rod &
Corner set by standard C. Description of monument for Set 3' of red-top 7" R. Pine 6" Twn. R.	rey procedure for and survey procedure recorner and accessories of the survey procedure recorner and accessories of the survey s	the subdivision of sections of the subdivision of the subdivision of the subdivision of the stablished to perpetuate locating the section of the subdivision of the stablished to perpetuate locating the section of the subdivision of section of the subdivision of section of the subdivision of sections of the subdivision of sections of the subdivision of sections of the subdivision of the subd	ons. f sections. he position of the corner: rod &
Corner set by standard C. Description of monument for Set 3' of red-top 7" R. Pine 6" Twn. R. SIGNED BY	rey procedure for and survey procedure recorner and accessories of the survey procedure recorner and accessories of the survey s	the subdivision of sections of the subdivision of sections of the subdivision of sections the stablished to perpetuate locating the section of the subdivision of the stablished to perpetuate locating the section of the section of the subdivision of sections of the subdivision of	ons. f sections. he position of the corner: rod &
Corner set by standard C. Description of monument for Set 3' of red-top 7" R. Pine 6" Twn. R.	r corner and accessories of the survey procedure of the survey o	the subdivision of sections of the subdivision of the subdivision of the subdivision of the stablished to perpetuate locating the section of the subdivision of sections of the subdivision of sections of the subdivision of	ons. f sections. he position of the corner: rod &
Corner set by standard C. Description of monument for Set 3' of red-top 7" R. Pine 6" Twn. R. SIGNED BY SURVEYOR'S MICHIGAN REGIONS STATE AND UNITED STATE AN	r corner and accessories of the survey procedure for a corner and accessories of the survey procedure for a corner and accessories of the survey procedure for a corner and accessories of the survey survey and the survey survey survey survey and the survey	the subdivision of sections of the subdivision of the subdivision of sections of the subdivision of sections of the subdivision o	ons. f sections. he position of the corner: rod & OW 24.9 OW 51.1 KENNETH J. OSTLING LAND SUPERIOR 10068
Corner set by standard C. Description of monument for Set 3' of red-top 7" R. Pine 6" Twn. R. SIGNED BY SURVEYOR'S MICHIGAN REGIONS STATE AND UNITED STATE SIGNED BY	r corner and accessories of the survey procedure for the survey procedure for the survey procedure for the survey procedure for the survey party chief of survey party chief of survey party	the subdivision of sections of the subdivision of the subdivision of the subdivision of the stablished to perpetuate locating the section of the subdivision of sections of the subdivision of sections of the subdivision of	ons. f sections. he position of the corner: rod & OW 24.9 OW 51.1 KENNETH J. OSTLING LAND LAN

CRAWFURD