

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____ N. _____ R. _____ E. _____		
2. PROPERTY CONTROLLING IN SECTION <u>2</u> T. <u>26</u> N. <u>X</u> R. <u>2</u> E. <u>X</u>		1; 4;
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ R. _____ E. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl R. Johnson, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on October 23, 19 84, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 1 Set corner mid-way and on line between section corner to west and 1/4 corner to east.
- 4 Found corner in place by George D. Henning 1952.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<p style="text-align: center;">1</p> <p>5/8" ironbar, next to found axle shaft</p> <p>10" red oak S 57° East 34.6'</p> <p>4" jack pine S 54° West 32.6'</p> <p>Cedar Post South 15.0'</p>	<p style="text-align: center;">4</p> <p>Found 1" x 36" axle shaft</p> <p>12" oak S60°E 44.5'</p> <p>4" jack pine S55°W 10.8'</p> <p>12" oak S30°E 47.2' Henning Survey 1952</p>
---	---


SIGNED BY Carl R. Johnson DATE 4/3/86

SURVEYOR'S MICHIGAN REGISTRATION NO. 30083

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE _____



SURVEYOR'S MICHIGAN REGISTRATION NO. _____ Crawford Count