

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 26 <sup>N.</sup> <sub>•</sub> , R. 3 <sup>W.</sup> <sub>•</sub>	A-11; A-12; A-13
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ <sup>N.</sup> <sub>•</sub> , R. _____ <sup>E.</sup> <sub>•</sub>	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ <sup>N.</sup> <sub>•</sub> , R. _____ <sup>E.</sup> <sub>•</sub>	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 15, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- A-11 Previously established by M. Schaaf in 1946 survey.
- A-12 Corner previously established by M. Schaaf in 1946 survey.
- A-13 Found railroad spike set by N. Parker in previous survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-11	A-12	Railroad Spike
Set DNR monument & red-top post	Set DNR monument & red-top post	11" R. Oak N42°W 83.05
10" R. Oak N53°W 30.0	7" R. Oak N78°W 19.95	12" R. Oak N30°E 64.2
8" R. Oak S24°W 19.5	6" W. Oak S18°W 23.5	

SIGNED BY Kenneth J. Ostling DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_