LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 26 N. S., R. 3 E. W.	M-9;M-7;M-10;M-8
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl R. Johnson, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 16, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

M-10

Found ½" bar & set post

7" Jack Pine	N28°W	18.9'
5" Jack Pine	N80°W	19.0'
5" Jack Pine	S50°W	7.7'

M-8

Found 3/4" pipe & set post

7" Jack Pine	N40°E	16.6'
6" Jack Pine	S3°E	25.1'
8" Jack Pine	S65°W	25.2'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-9 - Found 3/4" pipe in place used in survey by G.D. Henning in Section 19.

M-7 - Found corner in place as used by G.D. Henning's survey in Section 19, T26N, R2W.

M-10 - Found ½" bar as established in G.D. Henning's survey in Township to east.

M-8 - Found 3/4" pipe in place as per G.D. Henning's survey of Section 19, T26N, R2W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-9

Found 3/4" Pipe

6" Jack Pine	S70°E	22.1'
8" Jack Pine	N55°E	43.5'
6" Jack Pine	N19°W	33.8'

M-7

Found 3/4" bar

12" Jack Pine	N26°E	29.1'
8" Jack Pine	S36°W	44.0'
12" Red Oak	N65°W	26.5'

SIGNED BY Carl R. Johnson DATE 9/3/85

STATE OF MICHIGAN CARL R. JOHNSON LAND SURVEYOR No. 30083 LICENSED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 30083

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CRAWFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET