

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>27</u> N. R. <u>1</u> ●	F-5; G-5
2. PROPERTY CONTROLLING IN SECTION <u>9</u>	, T. <u>27</u> N. R. <u>1</u> ●	11; 12
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ S. R. _____ ●	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

Crawford

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on May 14, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- F-5 Found concrete monument set in G.F.D. survey of Section 16.
- G-5 Found Houghton tile at corner used in Henning survey of Section 15 & G.F.D. survey of Section 16.
- 11 Set by standard survey procedure for subdivision of sections.
- 12 Set by standard survey procedure for subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-5	G-5	11
Left 4" concrete monument w/¼" rebar in place	6" concrete filled tile w/½" rebar	2½' of 1" pipe & cedar post
11" Oak S05°E 49.3	7" Oak w/RLS cap 2240 S53°E 70.1	12" Cedar N80°W 22.6
6" Oak N82°E 71.0	10" J. Pine w/RLS cap 2240 N43°E 58.8	8" Cedar N45°W 11.3
		12
		2½' of 1" pipe
		14" Cedar N47°W 13.7
		12" Cedar N17°E 25.0


SIGNED BY Kenneth J. Ostling DATE 6-15-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CRAWFORD COUNTY