## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	LOCATED IN -:	l	CORNER	CODE NUMBER		
1. PUBLIC LAND SURVEY	T. <u>27</u> ♠, R	1 .	A-10; A-	11; B-11		
2. PROPERTY CONTROLL- ING IN SECTION —	N, T S., R	E. W.		<del></del>		
3. MISCELLANEOUS PROPERTY IN SECTION—			<del></del>	<u> </u>	   	
4. LOT NO , RE	CORDED PLAT					
5. PRIVATE CLAIMS		<u>.</u>				DF DEEDS STAMP AND
I, Kenneth J. Ost the corner points mentioned in re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field sur as expressed below and in confi Decree of a Court of law:	e-monumented, recover in the current manual or by a decree of a cour vey on	ere, in a fired or restored or restored of surveyert of law.	ield survey of tored as exp instructions Furthermore 9, four	on June pressed below and s of the United S e, that the corne and, recovered, res	19, I in conform States Depar er points me tored, establ	, 19 <u>75</u> , established nance with regulation tment of the Interior ntioned in lines 3, ished or re-established
A. Description of original mor	nument and accessories	and/or su	bsequent res	storation:		
B. Description of corner eviden	nce found and/or meth	nod applied	d in restorin	g or re-establishit	ng corner:	
A-10 Set corner by propose A-11 Reset Schaaf monumen	rtionate measure	ment be	tween se	ction corner	-	
A-10 Set corner by propose  A-11 Reset Schaaf monumer  B-11 Set by proportionate  C. Description of monument for A-10  Set The DNR monument  4" R. Pine S46°W 27.3	rtionate measurer  Int in his location  E measurement be  or corner and accessoric  A:  1½" Pipe/Conc. 18" R. Pine	ment be on.  tween s  es establish -11 . Base N73°E N20°E South	ection content to perpendicular to perpe	ction corner orners. tuate locating the	position of B-11 nument, p	rop. & on line
A-10 Set corner by proport  A-11 Reset Schaaf monumer  B-11 Set by proportionate  C. Description of monument for  A-10  Set DNR monument  4" R. Pine S46°W 27.3  6" R. Pine N80°W 35.3  Cedar Post West 8"  SIGNED BY  SURVEYOR'S MICHIGAN RE	rtionate measurer it in his location in the measurement be browner and accessoric  A:  1'4" Pipe/Conc. 18" R. Pine 8" Oak 1" Iron Bar Cedar Post  GISTRATION NO.	ment be on.  tween s  es establish -11 . Base N73°E N20°E South North	tween served to perpendicular to perpend	ction corner orners.  tuate locating the Set DNR mo 7" Cedar 6" Cedar Cedar Post	position of B-11 nument, p	rop. & on line
A-10 Set corner by proport  A-11 Reset Schaaf monumer  B-11 Set by proportionate  C. Description of monument for  A-10  Set DNR monument  4" R. Pine S46°W 27.3  6" R. Pine N80°W 35.3  Cedar Post West 8'  SIGNED BY  SURVEYOR'S MICHIGAN RE  FOR STATE AND UNITED S	rtionate measurer it in his location in the measurement be be measurement be corner and accessoric  A.  1½" Pipe/Conc. 18" R. Pine 8" Oak 1" Iron Bar Cedar Post  GISTRATION NO TATES AGENCIES:	ment be on.  tween s es establish -11 . Base N73°E N20°E South North	ection contact the desired to perpendicular to perpendicular to the desired	tuate locating the Set DNR mo 7" Cedar 6" Cedar Cedar Post	position of B-11 nument, p S40°E S60°W South  KENNE J. OSTLI LAND SURVEY No. 10068	rop. & on line 25.2 22.5 15'
A-10 Set corner by proport  A-11 Reset Schaaf monumer  B-11 Set by proportionate  C. Description of monument for  A-10  Set DNR monument  4" R. Pine S46°W 27.3  6" R. Pine N80°W 35.3  Cedar Post West 8"  SIGNED BY  SURVEYOR'S MICHIGAN RE	rtionate measurer of in his location e measurement be or corner and accessorie  A: 1½" Pipe/Conc. 18" R. Pine 8" Oak 1" Iron Bar Cedar Post  GISTRATION NO TATES AGENCIES:	ment be on.  tween s  es establish -11 . Base N73°E N20°E South North	tween served to perpert 118.9 63.85 33.0 15'	tuate locating the Set DNR mo 7" Cedar 6" Cedar Cedar Post	position of B-11 nument, p S40°E S60°W South  OF A KENNE J. OSTLI LAND SURVEY NO. 10068	rop. & on line 25.2 22.5 15'