

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. <u>27</u> <sup>N.</sup> <u>1</u> <sup>W.</sup>	B-9; C-9; C-10; C-11
2. PROPERTY CONTROLLING IN SECTION_____	, T. _____ <sup>N.</sup> <sup>S.</sup> , R. _____ <sup>E.</sup> <sup>W.</sup>	_____
3. MISCELLANEOUS PROPERTY IN SECTION_____	, T. _____ <sup>N.</sup> <sup>S.</sup> , R. _____ <sup>E.</sup> <sup>W.</sup>	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on December 28, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- B-9 Found corner as established by M. Schaaf in 1934 survey, by proportionate measurement.
- C-9 Recovered corner as restored in 1930's survey by M. Schaaf from U.S.B.T.'s original corner.
- C-10 Found corner as restored by M. Schaaf in 1934 survey from U.S.B.T.
- C-11 Found corner as restored by M. Schaaf in 1934 survey from Newman N.B.T.'s, now gone.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-9	C-9	C-10
DNR mon. & red-top post	1½" pipe in conc. block	1" pipe
4" J. Pine N43°W 20.3	6" J. Pine N86°W 12.5	7" J. Pine N44°E 41.8
8" J. Pine N70°E 25.0	4" R. Pine N25°W 51.0	6" J. Pine N40°W 25.85
	*22" R. Pine South 23.0	
	*U.S.B.T.	
		C-11
		1½" pipe in conc. & red-top post
		20" R. Pine N54°E 14.0
		16" R. Pine N83°W 66.2


SIGNED BY Kenneth J. Ostling DATE 12-12-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

CRAWFORD COUNTY