LAND CORNER RECORDATION CERTIFICATE ,

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY.	6 т. <u>27 </u> х ., к. <u>1</u> }	C-2:	-
2. PROPERTY CONTROLL- ING IN SECTION-	6,T. 27 8., R. 1	<u>_2;</u>	-
3. MISCELLANEOUS PROPERTY IN SECTION	6 ,T. 27 N. R1	*	
4. LOT NO,	RECORDED PLAT		
5. PRIVATE CLAIMS	·		REGISTER OF DEEDS STAMP AND
the corner points mentioned re-established, monumented and rules therefore as requibureau of Land Managemer and 5 above were, in a field as expressed below and in a Decree of a Court of law:	in lines I and 2 above were, in , re-monumented, recovered or red in the current manual of sunt or by a decree of a court of la survey on	a field survey on <u>Septembe</u> restored as expressed below a vey instructions of the United w. Furthermore, that the corn_, 19, found, recovered, re-	s of P.A. 74, Michigan P.A. of 1970, r 10, 19.85 _, established, and in conformance with regulations. States Department of the Interior, ner points mentioned in lines 3, 4 estored, established or re-established stration for Land Surveyors or, by a
See Continued A. a kaning kaning A. A	ния направания выправания в при	x moi textot en son sende ex	
9			
Set 5/8" rod w/c 6" jack pine N3 8" white pine N5	31 ^o E 35.2'		
B. Description of corner ev 2 Set midway and or	idence found and/or method ap n line between section place as used in previo	corner to East and 1/	
B. Description of corner ev 2 Set midway and or C-2 Found corner in p		corner to East and 1/	4 Corner to West.
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/ca	a line between section place as used in previous survey procedure for su at for corner and accessories esta up and post power pole	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating t C-2 Found 15" pipe by Se	the position of the corner:
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/ca	olace as used in previous survey procedure for sunt for corner and accessories estant pand post power pole" S32° W 70.2' S51°E 39.3'	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating t C-2 Found 1½" pipe by Se set post (old withe 6" jack pine N436 6" jack pine S316	the position of the corner: chaaf ess tree) W 8.2' W 19.7'
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monumer 2 Set 5/8""rod w/ca reference marker 12" red pine 10" red oak SIGNED BY Arc. SURVEYOR'S MICHIGAN FOR STATE AND UNITED	a line between section place as used in previous survey procedure for survey size of su	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating to C-2 Found 1½" pipe by Sest post (old withe 6" jack pine N436" jack pine S3168" Ref. Marker East	the position of the corner: chaaf ess tree) W 8.2' W 19.7' st 50.2' CARL R. JOHNSON LAND
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/careference marker 12" red pine 10" red oak SIGNED BY Arc. SURVEYOR'S MICHIGAN FOR STATE AND UNITED SIGNED BY.	n line between section place as used in previous survey procedure for su at for corner and accessories esta ap and post power pole" \$32° W 70.2' \$51°E 39.3' N2°W 30.3' REGISTRATION NO30 D STATES AGENCIES:	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating to C-2 Found 1½" pipe by Seset post (old withe 6" jack pine N43' 6" jack pine S31' 8" Ref. Marker East DATE DATE DATE	the position of the corner: chaaf ess tree) W 8.2' W 19.7' st 50.2' CARL R. JOHNSON LAND SURVEYOR SURVEYOR SURVEYOR JOHNSON LAND SURVEYOR LAND SURVEYOR JOHNSON JOHN
B. Description of corner ev 2 Set midway and or	line between section	corner to East and 1/	
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/ca	a line between section place as used in previous survey procedure for su at for corner and accessories esta up and post power pole	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating t C-2 Found 15" pipe by Se	4 Corner to West. the position of the corner:
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/ca	a line between section place as used in previous survey procedure for su at for corner and accessories esta up and post power pole	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating t C-2 Found 1½" pipe by Se set post (old withe 6" jack pine N436 6" jack pine S316	the position of the corner: chaaf ess tree) W 8.2' W 19.7'
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/ca	a line between section place as used in previous survey procedure for su at for corner and accessories esta up and post power pole	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating t C-2 Found 1½" pipe by Se set post (old withe 6" jack pine N436 6" jack pine S316	the position of the corner: chaaf ess tree) W 8.2' W 19.7'
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/careference marker 12" red pine 10" red oak SIGNED BY Arc. SURVEYOR'S MICHIGAN FOR STATE AND UNITED	a line between section place as used in previous survey procedure for survey size of su	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating to C-2 Found 1½" pipe by Sest post (old withe 6" jack pine N436" jack pine S3168" Ref. Marker East	the position of the corner: chaaf ess tree) W 8.2' W 19.7' st 50.2' CARL R. JOHNSON LANO LANO LANO LANO LANO LANO LANO LA
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monumer 2 Set 5/8""rod w/ca reference marker 12" red pine 10" red oak SIGNED BY Arc. SURVEYOR'S MICHIGAN FOR STATE AND UNITED	a line between section place as used in previous survey procedure for survey size of su	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating to C-2 Found 1½" pipe by Sest post (old withe 6" jack pine N436" jack pine S3168" Ref. Marker East	the position of the corner: chaaf ess tree) W 8.2' W 19.7' st 50.2' CARL R. JOHNSON LAND
B. Description of corner ev 2 Set midway and or C-2 Found corner in p 9 Set by standard s C. Description of monument 2 Set 5/8""rod w/careference marker 12" red pine 10" red oak SIGNED BY Arc. SURVEYOR'S MICHIGAN FOR STATE AND UNITED SIGNED BY.	n line between section place as used in previous survey procedure for su at for corner and accessories esta ap and post power pole" \$32° W 70.2' \$51°E 39.3' N2°W 30.3' REGISTRATION NO30 D STATES AGENCIES:	corner to East and 1/2 us surveys. bdivision of sections blished to perpetuate locating to C-2 Found 1½" pipe by Seset post (old withe 6" jack pine N43' 6" jack pine S31' 8" Ref. Marker East DATE DATE DATE	the position of the corner: chaaf ess tree) W 8.2' W 19.7' st 50.2' CARL R. JOHNSON LAND