

Lawrence E. ...

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	_____
2. PROPERTY CONTROLLING IN SECTION <u>26</u>	, T. <u>27</u> N. R. <u>2</u> W.	<u>10</u>
3. MISCELLANEOUS PROPERTY IN SECTION <u>26</u>	, T. <u>27</u> N. R. <u>2</u> W.	<u>I-9/3; I-10/3</u>
4. LOT NO. _____	, RECORDED PLAT _____	_____
5. PRIVATE CLAIMS _____	_____	_____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on September 20, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on September 20, 1978, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:


B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 10** Set corner by standard survey procedure for the subdivision of sections.
- I-9/3** Set corner by standard survey procedure for the subdivision of sections.
- I-10/3** Set corner by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

	I-9/3	I-10/3
Set 5/8" Rod w/RLS Cap & Cedar post	Set 5/8" Rod w/RLS Cap & cedar post	Set 5/8" Rod w/RLS Cap & ced. post
4" R. Oak N66°W 24.65	8" Oak S48°W 13.4	8" J. Pine N63°W 28.18
11" R. Oak S39°W 14.65	4" Oak N58°W 18.1	4" W. Oak N09°W 16.15

SIGNED BY *Kenneth J. Ostling* DATE 11-15-78
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CRAWFORD COUNTY