

Crawford ✓

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>27</u> N. <u>8</u> , R. <u>4</u> <u>W.</u>	K-1 K-3 L-3
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. _____ S., R. _____ E. _____ W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ S., R. _____ E. _____ W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on Oct. 17 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:


- K-1** Restored corner as established by Newman in early 1900 survey.
- K-3** Found 1/2" pipe as established in previous survey by unknown.
- L-3** Found 1/2" re-rod in old corner fence post bottom. Old Hemlock stub scribed NBT facing corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-1	K-3	L-3
Set DNR Monument	Set DNR Monument	Set DNR Monument
6" W. Pine S02E 81.5'	7" W. Pine S63E 47.8'	5" Stem Tw H. Maple N83E 8.2'
3" W. Pine N53E 21.7'	3" W. Pine N35E 42.0'	6" H. Maple N05E 20.3'
18" R. Pine N37W 96.9'		Hem. Stub scribed
26" W. Pine stp N08W 26.3'		NBT
		S37E 73.3'

SIGNED BY Kenneth J. Ostling DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____