LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUM	BEK
1. PUBLIC LAND SURVEY 18	т. <u>27</u> . R. <u>4</u> . w.	A-6; A-7;	
2. PROPERTY CONTROLL-	N. S., R W.		
3. MISCELLANEOUS PROPERTY IN SECTION	N. E. W. W.		-
4. LOT 80, REC			
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in I re-established, monumented, re-and rules therefore as required. Bureau of Land Management or and 5 above were, in a field survas expressed below and in confe Decree of a Court of law:	ines 1 and 2 above were, in a monumented, recovered or r in the current manual of surv by a decree of a court of law rey on	estored as expressed be rey instructions of the U. Furthermore, that the 19, found, recove Michigan State Board of	ements of P.A. 74, Michigan P.A. of 1970. 6,, 1922, established elow and in conformance with regulation United States Department of the Interior in corner points mentioned in lines 3, ered, restored, established or re-established fregistration for Land Surveyors or, by
V. Description of original moun	ument and accessories and/or	subsequent restoration:	
	TIONATE MEASUREMENT	BETWEEN SECTION (
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE	TIONATE MEASUREMENT	BETWEEN SECTION (CORNERS.
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE	TIONATE MEASUREMENT	BETWEEN SECTION (M. SCHAAF. blished to perpetuate lo	cating the position of the corner:
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument f	TIONATE MEASUREMENT	BETWEEN SECTION (M. SCHAAF. blished to perpetuate logert DNR MONI IME	cating the position of the corner: A-7 NT
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the second	TIONATE MEASUREMENT TIN 1934 SURVEY BY for corner and accessories esta	BETWEEN SECTION (M. SCHAAF. blished to perpetuate logert DNR MONI IME	cating the position of the corner:
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the second	TIONATE MEASUREMENT TIN 1934 SURVEY BY for corner and accessories esta	BETWEEN SECTION (M. SCHAAF. blished to perpetuate logert DNR MONI IME	cating the position of the corner: A-7 NT
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for A-6 T DNR MONUMENT R. PINE S38°W 29.8 R. PINE N15°W 17.4	TIONATE MEASUREMENT TIN 1934 SURVEY BY for corner and accessories esta	BETWEEN SECTION (M. SCHAAF. blished to perpetuate log SET DNR MONUMER 711 R. PINE 511 R. PINE	cating the position of the corner: A-7 NT N20°W 32.8! N53°E 42.8! KENNETH KENNETH
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the same of the	TIONATE MEASUREMENT IT IN 1934 SURVEY BY for corner and accessories esta	BETWEEN SECTION (M. SCHAAF. blished to perpetuate local section of the perpetuate local sect	cating the position of the corner: A-7 NT N20°W 32.8¹ N53°E 42.8¹ KENNETH
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the second of monument for the second of the second o	TIONATE MEASUREMENT IT IN 1934 SURVEY BY for corner and accessories esta B! I Detle EGISTRATION NO. #100 STATES AGENCIES:	BETWEEN SECTION (M. SCHAAF. blished to perpetuate local section of the perpetuate local sect	CORNERS. Cating the position of the corner: A-7 NT N20°W 32.8' N53°E 42.8' KENNETH J. OSTLING SURVEYOR NO. 10068 AND SURVEYOR
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the second of monument for the second of the second o	TIONATE MEASUREMENT IT IN 1934 SURVEY BY for corner and accessories esta B! I Detle EGISTRATION NO. #100 STATES AGENCIES:	BETWEEN SECTION (M. SCHAAF. blished to perpetuate local section of the perpetuate local sect	CORNERS. Cating the position of the corner: A-7 NT N20°W 32.8' N53°E 42.8' KENNETH J. OSTLING SURVEYOR NO. 10068 AND SURVEYOR
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the second of monument for the second of the second o	TIONATE MEASUREMENT IT IN 1934 SURVEY BY for corner and accessories esta B! I Detle EGISTRATION NO. #100 STATES AGENCIES:	BETWEEN SECTION (M. SCHAAF. blished to perpetuate local section of the perpetuate local sect	CORNERS. Cating the position of the corner: A-7 NT N20°W 32.8' N53°E 42.8' KENNETH J. OSTLING SURVEYOR NO. 10068 AND SURVEYOR
SET CORNER BY PROPOR FOUND 1 1/2" PIPE SE C. Description of monument for the second of monument for the second of the second o	TIONATE MEASUREMENT IT IN 1934 SURVEY BY for corner and accessories esta B! I Detle EGISTRATION NO. #100 STATES AGENCIES:	BETWEEN SECTION (M. SCHAAF. blished to perpetuate local section of the perpetuate local sect	cating the position of the corner: A-7 NT N20°W 32.8¹ N53°E 42.8¹ KENNETH