LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:			CORNER CODE NUMBER		
L PUBLIC LAND SURVEY	1. 28	3 - N. R. 1	.	$G = 2^{2}$; $H = 2^{2}$; $H = 3^{2}$; $I = 2^{2}$		
2. PROPERTY CONTROLLS ING INSECTION	.1.	N. S., R.	I: . W .			
3. MISCLELANEOUS PROPERTY IN SECTION	т.	N. S., R.	l'.			
4. LOT NO	ORDED PL	AΤ				
S DDINATE A LARGE						

5, PRIVATI CLAIMS:

1

REGISTER OF DEFDS STAMP AND FILING NUMBER

C. CONTINUED:

11-3			1-2				
SET DNR MONUMENT			SET DNR	MONUME	NT		
10" JACK PINE	\$32°E	22.0'	7" JACK	PINE	540°W	26.2'	
10" JACK PINE	N57°E	18.1'	6" JACK	PINE	พ ^๑ อ อห	29.1	

- B. Description of corner evidence found and or method applied in restoring or re-establishing corner:
- G-2 RESET MONUMENT AS ESTABLISHED IN A PREVIOUS DNR SURVEY FROM WITNESSES OF RECORD.
- H-2 SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS AT THE CALCULATED INTERSECTION OF THE TRUE 1/4 LINES.
- H-3 SET CORNER BY PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS.
- 1-2 SET CORNER BY PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS. FOR SOME UNUSUAL REASON THE U.S. FIELD NOTES PLACE THIS CORNER AT MIDPOINT RATHER THAN 40 CHAINS FROM SOUTH, SO IT WAS RESIORED IN THAT MANNER.
 - C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>G-2</u>	H- 2
SET DNR MONUMENT	SET 5/8" ROD W/RLS CAP
20" R. PINE N50°E 33.7"	6" JACK PINE S10°W 11.5"
14" R. PINE N55°W 7.3'	6" JACK PINE 5510F 28 41

SIGNED BY Kluults & Orthing

SUBVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

DATE

APPROVED AND SIGNED BY,

DATE.

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SUBVEYOR'S MICHIGAN BEGISTRATION NO

CPAWFORD COUNTY

SEAMO SURTAIN