LAND CORNER RECORDATION CERTIFICATE

Set at calculated intersection of true ½ lines, per standard survey procedure. Set by standard survey procedure for the subdivision of sections. Set by standard survey procedure for the subdivision of sections. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner in the subdivision of sections. F-12 Set DNR Monument Set 2½' of 1" pipe Set 2½' of 1" pipe & red top post 10" H. Maple N64W 9.7' Set DNR Monument 10" H. Maple N08W 5.7' 6" H. Maple N64W 9.7'		REQUIREMENT	Of Motor Control	i
1. PUBLIC LAND SURVEY T. 28 S. R. 4 S. S. J. 2. S. J. 3. MISCELLANEOUS PROPERTY IN SECTION. T. S. R. S. J. 2. S				1 out
2. PROPERTY CONTROLL. 1. SING IN SECTION. 2. PROPERTY CONTROLL. 3. MESCELLANBEOUS PROPERTY IN SECTION. 2. PROPERTY IN SECTION. 3. R. S. R. J. S. J. S. R. J. S. J. S. R. J. S. J. S. R. J. S. R. J. S. R. J. S. R. J. S. J. S. R. J. S. R. J. S. J. S. R. J. S. J. S. R. J.	FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBE	R
2. PROPERTY CONTROLL: 33 T. 28 N. R. 4 S. 12 3. MISCELLANGEOUS PROPERTY IN SECTION	1. PUBLIC LAND SURVEY	T. 28 N. R. 4 W.	E-12; F-12	
3. MSCELLANEOUS PROPERTY IN SECTION T. S. R. S.	2. PROPERTY CONTROLL- 33	T. 28 N. R. 4 W.	5; 12	
5. PRIVATE CLAIMS 1. Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on November 13. 1973, established, recentablished, monumented, reconvered or field survey on November 14. 1973, established, recentablished, monumented, reconvered or survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 3 above were, in a field survey or court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 3 above were, in a field survey or court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 3 above were, in a field survey or formance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court or law. A. Description of original monument and accessories and/or subsequent restoration: B. Description of original monument and accessories and/or subsequent restoration: Corner set by proportionate measurement between section corners. Set by standard survey procedure for the subdivision of sections. Set by standard survey procedure for the subdivision of sections. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories stablished to perpetuate locating the position of the corner section of monument for corner and accessories established to perpetuate locating the position of the corner section of monument for corner and accessories established to perpetuate locating the position of the corner section of monument for corner and accessories established to perpetuate locating the position of the corner section of monument for corner and accessories established to perpetuate locating the position of the corner section of monument for corner and accessories established	3. MISCELLANEOUS PROPERTY IN SECTION	,T N. R E.		
I. Kenneth J. Ostling do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on November 13, 1973, established, re-established, anomented, re-monumented, recovered or field survey below and in conformance with regulations and rules therefore as required in the current manual restored as expressed below and in conformance with regulations and rules therefore as required in the current manual restored as expressed below and in conformance with regulations and rules therefore as required in the current manual restored as expressed below and in conformance with the current manual policy of the polic	4. LOT NO, RECOR	DED PLAT		CTAMB AND
the corner points mentioned in lines 1 and 1982 at abilished, re-established, monumented, recovered in the current manual restored as expressed below and in conformance with regulations and rules therefore as required in the current manual restored as expressed below and in conformance with regulations and rules therefore as required in the current manual restored as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Management or by a decree of a court of law: A. Description of corner evidence found and/or method applied in restoring or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law: A. Description of original monument and accessories and/or subsequent restoration: B. Description of original monument and accessories and/or subsequent restoration: Corner set by proportionate measurement between section corners. Set at calculated intersection of true k lines, per standard survey procedure. Set by standard survey procedure for the subdivision of sections. Set by standard survey procedure for the subdivision of sections. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner set. B. Description of monument for corner and accessories established to perpetuate locating the position of the corner set. C. Description of monument set set 2½ of 1" pipe S	5. PRIVATE CLAIMS			FILING NUMBER
Set at calculated intersection of true & lines, per standard survey procedure. Set by standard survey procedure for the subdivision of sections. Set by standard survey procedure for the subdivision of sections. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner below the subdivision of sections. F-12 Set DNR Monument Set 2½' of 1" pipe Set 2½' of 1" pipe & Set 2½' of 1" pipe & red top post 8" Maples S77W 9.45' 10" H. Maple N08W 5.7' 6" H. Maple N06W 9.7' 8" H. Maple N05E 14.8' 33" W.P. Stub S19E 75.0' 7" H. Maple N87W 9.9' 8" H. Maple N05E 14.8' 33" W.P. Stub S19E 75.0' 7" H. Maple N87W 9.9' 8" H. Maple S74W 23.90' 10" M. Maple S74W 23.90' 1	formance with the rules of the law:	Michigan State Board of	Registration for Land St	urveyors or, by a Decree of a Court of
Set by standard survey procedure for the subdivision of sections. 12 Set by standard survey procedure for the subdivision of sections. 13 Set by standard survey procedure for the subdivision of sections. 14 C. Description of monument for corner and accessories established to perpetuate locating the position of the corner sections. 15 Set DNR Monument 16 Set 2½' of 1" pipe 17 Set DNR Maples S77W 9.45' 10" H. Maple N08W 5.7' 6" H. Maple N64W 9.7' 18 Maples S77W 9.45' 10" H. Maple N87W 9.9' 8" H. Maple N05E 14.8' 19 Set 2½' of 1" pipe 10 S				
Set by standard survey procedure for the subdivision of sections. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of th	a hir nyonor	tionate measuremen	it between section	corners.
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate location and acc	Corner set by propor	tionate measurement entersection of true	nt between section e ¼ lines, per stan	dard survey procedure.
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner E-12 Set DNR Monument Set 2½' of 1" pipe Set 2½' of 1" pipe Set 2½' of 1" pipe & red top post 8" Maples S77W 9.45' 10" H. Maple N08W 5.7' 6" H. Maple N64W 9.7' 33" W.P. Stub S19E 75.0' 7" H. Maple N87W 9.9' 8" H. Maple N05E 14.8' Set 2½' of 1" pipe 8" H. Maple S17W 40.6' 8" H. Maple S74W 23 91 8" H. Maple S74W	Corner set by propor Set at calculated in	tionate measurement entersection of true vey procedure for	nt between section Light lines, per stan the subdivision of	dard survey procedure.
E-12 F-12 Set 2½' of 1" pipe Set 2½' of 1" pipe & red top post	-12 Corner set by propor -12 Set at calculated in	tionate measurement entersection of true vey procedure for	nt between section Light lines, per stan the subdivision of	dard survey procedure.
Set DNR Monument Set 2½' of 1" pipe Set 2½' of 1" pipe 4 Ted top pool 8" Maples S77W 9.45' 10" H. Maple N08W 5.7' 6" H. Maple N64W 9.7' 33" W.P. Stub S19E 75.0' 7" H. Maple N87W 9.9' 8" H. Maple N05E 14.8' Set 2½' of 1" pipe 8" H. Maple S17W 40.6' 8" H. Maple S74W 23 91.00 (in clump) SIGNED BY Level Document of the company of	-12 Corner set by propor -12 Set at calculated in 5 Set by standard surv 12 Set by standard surv	etionate measurement ntersection of true vey procedure for the vey procedure for	at between section $e^{\frac{1}{4}}$ lines, per stan the subdivision of the subdivision of	dard survey procedure. sections. sections.
Set 2½' of 1" pipe 8" H. Maple S17W 8" H. Maple S74W (in clump) SIGNED BY Lenneth Outling DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 FOR STATE AND UNITED STATES AGENCIES:	-12 Corner set by propor -12 Set at calculated in 5 Set by standard surv 12 Set by standard surv	rtionate measurement ntersection of true vey procedure for the vey procedure for the for corner and accessor	the subdivision of	dard survey procedure. sections. sections. nate locating the position of the corne
SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 SURVEYOR FOR STATE AND UNITED STATES AGENCIES:	Corner set by propor Set at calculated in Set by standard surv Set by standard surv C. Description of monument E-12 Set DNR Monument Maples S77W 9.45'	rtionate measurement ntersection of true vey procedure for vey procedure for for corner and accessor F-12 Set 2½' of 1" p 10" H. Maple	the subdivision of the subdivisi	dard survey procedure. sections. sections. ate locating the position of the corne 5 2' of 1" pipe & red top post Maple N64W 9.7'
SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 SURVEYOR FOR STATE AND UNITED STATES AGENCIES:	Corner set by propor Set at calculated in Set by standard surv Set by standard surv C. Description of monument E-12 Set DNR Monument Maples S77W 9.45'	rtionate measurement ntersection of true vey procedure for vey procedure for for corner and accessor F-12 Set 2½' of 1" p 10" H. Maple	the subdivision of the subdivisi	dard survey procedure. sections. sections. ate locating the position of the corne 5 1' of 1" pipe & red top post Maple N64W 9.7' Maple N05E 14.8' e W 40.6'
FOR STATE AND UNITED STATES AGENCIES:	Corner set by propor Set at calculated in Set by standard surv Set by standard surv C. Description of monument E-12 Set DNR Monument 8" Maples S77W 9.45' 33" W.P. Stub S19E 75.0'	rtionate measurement ntersection of true vey procedure for vey procedure for for corner and accessor F-12 Set 2½' of 1" p 10" H. Maple N 7" H. Maple N	the subdivision of the subdivisi	dard survey procedure. sections. sections. ate locating the position of the corne 5 1' of 1" pipe & red top post Maple N64W 9.7' Maple N05E 14.8' e W 40.6' W 23.91
THE WEST AND	Corner set by propor Set at calculated in Set by standard surv Set by standard surv C. Description of monument E-12 Set DNR Monument 8.8" Maples S77W 9.45' 33" W.P. Stub S19E 75.0'	rtionate measurement resection of true vey procedure for vey procedure for for corner and accessor F-12 Set 2½' of 1" p 10" H. Maple N 7" H. Maple N	the subdivision of the subdivisi	dard survey procedure. sections. sections. ate locating the position of the corne 5 1' of 1" pipe & red top post Maple N64W 9.7' Maple N05E 14.8' e W 40.6' W 23.91

SURVEYOR'S MICHIGAN REGISTRATION NO. ____ FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 DISTRIBUTED BY MICHIGAN BOCIETY OF REGISTERED LAND SURVEYORS FORM NO. ML M736 POPE 1041 PROS. & CON RALAMAZOO, MICH.

APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR