

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>28</u> ^{N.} <input checked="" type="radio"/> _{S.} , R. <u>4</u> ^{W.} <input checked="" type="radio"/> _{E.}	E-7; E-8; E-10; E-11
2. PROPERTY CONTROLLING IN SECTION _____	T. _____, ^{N.} <input type="radio"/> _{S.} , R. _____, ^{E.} <input type="radio"/> _{W.}	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____, ^{N.} <input type="radio"/> _{S.} , R. _____, ^{E.} <input type="radio"/> _{W.}	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on November 5, 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-7 Corner established by double proportionate measurement. No evidence of a previous corner.
- E-8 Set corner by proportionate measurement between section corners.
- E-10 Set by proportionate measurement between section corners.
- E-11 Corner set by double proportionate measurement. No evidence of previous corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-7	E-8	E-10
Set DNR Monument	Set DNR Monument	Set DNR Monument
6" Maple S75W 16.6'	4" Maple S12W 12.3'	7" H. Maple S13W 23.75'
5" Maple S03W 10.6'	6" Maple S55W 29.6'	8" H. Maple S80E 19.4'
E-11		
Set DNR Mon. & red top post		
Tw. 5" Maples N19E 26.8'		
7" Maple S65W 6.5'		


SIGNED BY Kenneth J. Ostling DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)



SURVEYOR'S MICHIGAN REGISTRATION NO. _____