LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| A 19" MARKO - JAIN JIAH O MODIO NOCE VAIS 14 15 15 15 15 | F | OR CORNERS OF -: | LOCAT | ED IN-: | CORNER C | ODE NUMBER | | | |
|--|------------------------|--|---|--|--|--|--|--|--|
| 3. MISCELLAMEOUS ROPERTY IN SECTION T. S. R. E. 4. LOT NO. RECORDED PLAT 5. PRIVATE CLAIMS 1. Kannath J. Ostiling do hereby certify that under requirements of P.A. 74, Michigan P.A. of P. the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, field survey on Decomber 2.7 1913. established, re-established, monumented, remonumented, remonumented, remonumented of survey instructions of the United States Department of the Interior. Bureau of Land Management or by a decree court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 3 above were, in a field survey instructions of the United States Department of the Interior. Bureau of Land Management or by a decree court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 3 above were, in a field survey in 19—, found, recovered, restored, established or exestablished as expressed below and in formance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Coulaw: A. Description of original monument and accessories and/or subsequent restoration: B. Description of original monument and accessories and/or subsequent restoration: B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: F-6 Set at calculated Intersection of true it lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner is a standard survey procedure. F-6 8 CN Poscription of monument for corner and accessories established to perpetuate locating the position of the corner is a standard survey procedure. F-7 Phase and the rules of the Maple Notice 86.3' 10" Tw. Maple | 1 | . PUBLIC LAND SURV | EY т. <u>28</u> | N. R. 4 W. | F-5; F-6; | | | | |
| 4. LOT NO, RECORDED PLAT | 2 | . PROPERTY CONTRO | OLL- 16 ,T. 28 | N. R. 4 V. | 8; 9 | | | | |
| I, Kenneth J. Ostiling | 3 | . MISCELLANEOUS PROPERTY IN SECT | TON ,T | N E V. | | | | | |
| I, Kannath J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of I the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, field survey on | 4 | , LOT NO. | , RECORDED PL | AT | | | | | |
| the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, field survey onDecember 27 1973_, established, monumented, re-monumented, recover restored as expressed below and in conformance with regulations and rules therefore as required in the current may of survey instructions of the United States Department of the Interior, Bureau of Land Management of by a decree court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field surve | 5 | , PRIVATE CLAIMS | | | | | | | |
| A. Description of original monument and accessories and/or subsequent restoration: B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: F-5 Found Richardson's ‡" rod & both N. B.T.'s F-6 Set at calculated intersection of true ‡ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and acce | t f c c | he corner points mer field survey on Dec restored as expressed of survey instructions court of law. Fur formance with the rul | ntioned in lines 1 comber 27 1 below and in conf of the United State thermore, that the | and 2 above (ide 973, established formance with regites Department of corner points of covered restored. | entified with control of the control | ircles on index on the control of th | one diagram—over , re-monumented, required in the cu lanagement or by a bove were, in a fie s expressed below | recovered or reent manual decree of a ld survey on and in con- | |
| B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: F-5 Found Richardson's ½" rod & both N. B.T.'s F-6 Set at calculated Intersection of true ½ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessorie | _ | | | | 1/ | | | | |
| F-5 Found Richardson's ½" rod & both N. B.T.'s F-6 Set at calculated intersection of true ½ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetua | • | A. Description of orig | ginal monument and | i accessories an | a/ or subseque | it restoration. | | | |
| F-5 Found Richardson's ½" rod & both N. B.T.'s F-6 Set at calculated intersection of true ½ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetua | | | | | | | | | |
| F-5 Found Richardson's ½" rod & both N. B.T.'s F-6 Set at calculated intersection of true ½ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetua | | | | | | | | | |
| F-5 Found Richardson's ½" rod & both N. B.T.'s F-6 Set at calculated intersection of true ½ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetua | | | | | | | | | |
| F-5 Found Richardson's ½" rod & both N. B.T.'s F-6 Set at calculated intersection of true ½ lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetua | | | | | | | | | |
| F-6 Set at calculated intersection of true # lines. 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner in | | | | | | oring or re-establi | ishing corner: | | |
| 8 Set by standard survey procedure. 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the positio | F-5 | | | | | | | | |
| 9 Set by standard survey procedure. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories estab | F - 6 | Set at calculated intersection of true $\frac{1}{4}$ lines. | | | | | | | |
| C. Description of monument for corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate locating the position of the corner and accessories established to perpetuate location and accessories established to perpetuate location and accessories established to per | 8 | Set by standard survey procedure. | | | | | | | |
| F-5 DNR Mon. * 15" Beech - S43W 35.4' 6" Maple N60E 86.3' 10" Tw. Maple N21W 18.4 * 10" EIm- S26E 51.0' Tw. 6" Maples N73E 91.0 6" Maple S77W 8.5 4" Maple S52E 29.9 * J. Richardson NBT's P-6 2½' of 1" pipe 4" Maple N24E 55.0 12" Tw. Maple N83W 36.1 | 9 | Set by standa | rd survey proc | edure. | | | | | |
| F-5 DNR Mon. * 15" Beech - S43W 35.4' 6" Maple N60E 86.3' 10" Tw. Maple N21W 18.4 * 10" EIm- S26E 51.0' Tw. 6" Maples N73E 91.0 6" Maple S77W 8.5 4" Maple S52E 29.9 * J. Richardson NBT's P-6 2½' of 1" pipe 4" Maple N24E 55.0 12" Tw. Maple N83W 36.1 | | C. Description of mo | onument for corner | and accessories | established to | perpetuate locat | ting the position o | of the corner: | |
| 9 * J. Richardson NBT's 2½' of 1" pipe 4" Maple N24E 55.0 12" Tw. Maple N83W 36.1 | * 15" Bee * 10" Elm | sch - \$43W n- \$26E | 35.4' 6" Ma 51.0' Tw. 6 | of 1" pipe aple N60E 8 | 6.31 | 2½' of 1" p 10" Tw. Map | le N21W | 18.4 ¹ 8.5 | |
| 4" Maple N24E 55.0 12" Tw. Maple N83W 36.1 | · | | 29.9 | - | - • | | | | |
| SIGNED BY Leweth Joseling DATE March 12" 19 1817 | * J. Rich | nardson NBT's | | 4" Maple | N24E | | | | |
| | | SIGNED BY Lev | neth & | Oselin | 9 | DATE March | 12 0914/0/ | | |
| SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 KENNEALL | | SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 | | | | - KENNSENHA G | | | |
| FOR STATE AND UNITED STATES AGENCIES: LGEO SURVEYOR | | | | | | REG | | *: | |
| SIGNED BY DATE | | SIGNED BY | CHIEF | OF BURVEY PARTY | | _ DATE | 10098 | , rec | |
| APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR DATE | | APPROVED AND SIG | GNED BY | MICHIGAN REGISTERED | LAND SURVEYOR . | DATE | VYO TVIID 80 100 | | |

F-5