

## LIBER 002 PAGE 371

STATE OF MICHIGAN COUNTY OF CHARLEVOIX RECEIVED FOR RECORD

SEP 1 2 1995

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

95 JUH 29 AM 10: 06

For corners in	Filing Requirement of Act 74, Mich. P.A. 197		Olader B. Carle
CHARLEVOIX (County)	Located In:	Corner Code ##	REGISTER OF DEEDS SURVEY 중
1. Public Land Survey	T R		REWONUMBERTIES
<ol> <li>Property Controlling in Section</li> <li>Miscellaneous Property in Sec.</li> </ol>	T R  T R  S T R  S T R  S T R  S T R		SEP 1 2 1995  COMMISSION  Register of Deeds Stamp & File Number
I. ARTHUR R. RANGER do hereby certify that under requirement in lines 1 and 2 above were in current manual of survey instruct Management or by a decree of a above were in conformance with Court of Law; established, reexpressed below:	in a field survey on No.v., uirements of P.A. 74, Michigan P.A. conformance with regulations a ctions of the United States Depa Court of Law and/or that the corn the rules of the Michigan Board	. 19 94 A. of 1970, the corner points mentione and rules therefore as required in the artment of the Interior, Bureau of Lander points mentioned in tines 3, 4 and lof Land Surveyors or by a Decree of monumented, recovered, found a	2
1840- John Mullet	t, Surveyor set post 540 <sup>0</sup> W 411ks.	nd/or subsequent restoration: and witnessed; Beech	12" N41 <sup>O</sup> W 431ks;

P.K. set by D.N.R. surveyors.

1973 Gene Ostling, Surveyor recovered and used conner in his survey. See Liber 205,

page 481 Antrim County Records.

1976- Replaced "PK" from our 1970 survey with a 1/4" iron pin; corner falls in center of N-S b'top county road & in line with center of gravel road west and old fence east. One-eight line fence, 1/4 mile north (to W) is on split of distance between SW corner of Sec. 31 (four twp. corner) as estab. & recovered W1/4 corner of Sec. 31.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

See reverse side\*

1994- Found 1-1/4" iron pin in road intersection, and witnesses; Gravel road centerline to the West; Fits Carl Roser's survey of 1975. Corner was accepted.

& fraction of the Bearings of ARTHOYEN Man Junk 16,1945 P.A. 345 0F 1990

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found 1-1/4" iron pin © of gravel road West P.P. N38°W 42.63' P.P. N58°E 50.50' Fe. Post S58°E 63.92' Conc. Mon. East 32.96'

Found 1-1/4" iron pin as recorded in L.2, Pg.45, Charlevoix County, MI, and is accepted as the best available evidence of the position of the original corner.

ARTHUR R. RANGER ROFESSIONA SURVEYOR No. 31601 OFESSION

igned by	· Yarge
urvevor's Michigan License No	21/261

01/16/95

\_\_\_ Date \_\_



Cher. Abs. & Eng.

A. continued

Corner previously recovered & used by RLS Gene Ostling; Liber 205, page 481, Antrim County Corner Records. Witnessed: Drove 1-1/4"x30" Iron Pin; Conc. FAS Mon. Due E 33'; Set Cedar post w/loc. tag Due E 33'; P.P. (RLS face tag #12026) N43°W 42.45'; Anchor Pole (face tag 12026) N50°E 50.5'

Liber 205, Page 481 by Gene Ostling: Found PK nail--Accessories--1. West of concrete monument 33.0 feet and fence line East.

 Center line of County Rd. N&S and to the West PK nail was set by Carl Roser RLS (Dept. of Nat. Res.) in the process of staking section subdivisions in Warner Twp., Antrim County, Mich.

Witnesses: Fd. PK nail Mon 33.0' East 10" Elm S77°33'W P.P. N43°13'W 42.2' P.P. S38°E 50.9'