LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	
2. PROPERTY CONTROLLING IN SECTION 17	,T. 33 N. S., R. 4 E. W.	1;14;16
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 4, 19 85, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (Continued):

16

Drove 3/8" x 5' pipe w/RLS cap & set cedar post

5" White Birch	N35°W	30.3'
10" Tamarack	N45°E	57.8'
8" Elm	N75°E	12.6'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

1 - Establish NW cor of NE¼ of NW¼ of Sec. 17 per standard B.L.M. instructions. Equidistant & on line between NW cor & N¼ cor of Sec 17. Fits E.A. Robinson survey of Sec. 17 (1902).

14 - Establish NE corner of SE¼ of SE¼ of Sec. 17 per standard B.L.M. instructions.

16 - Establish SW corner of SE¼ of SE¼ of Section 17 per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1

Drove 5/8" x 34" rerod w/RLS cap & set cedar post w/loc tag

Power Pole	N22°W	41.36'
24" Cherry	N88°E	51.59'
6" Elm	S52°E	59.22'
Fd 1" pipe (rd. P.I. gr. rd. to S&W)	N77°03'55"E	9.34'

14

Drove 5/8" x 34" rerod w/RLS cap & set cedar post w/loc tag

14" Hemlock	N32°W	22.7'
11" Beech	S46°E	23.8'
23" Hemlock	S12°W	19.4'
Fd "T" iron w/RLS cap #3920	S88°30'E	6.49'

SIGNED BY Carl F. Roser 02-07-86 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CHARLEVOIX COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET