LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	_____
2. PROPERTY CONTROLLING IN SECTION 15	,T. 33 N. S., R. 5 E. W.	16, 15, 12, 11
3. MISCELLANEOUS PROPERTY IN SECTION _____	,T. _____ N. S., R. _____ E. W.	_____

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 18, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

12			11		
Set 5/8" x 36" rerod w/cap & cedar post			Set 5/8" x 36" rerod w/cap & cedar post		
Fd. T. Ir.	S06°25'W	6.17	Fd. T. Ir.	S54°10'E	9.36
10" Maple	S60°E	9.5	5" Ir. Wood	S50°E	15.1
7" Maple	S15°W	28.8	8" Maple (triple)	North	3.0
6" Maple	N55°W	37.8	13" Maple	S70°W	28.2

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

16 Estab. NW corner of NE¼ - NE¼ of Sec. 22 per std. BLM instructions.
15 Established SW corner of SE¼ - SW¼ of Sec. 15 per std. BLM instructions.
12 Established NE corner of SE¼ - SW¼ of Sec. 15 per std. BLM instructions.
11 Established ctr. of SW¼ of Sec. 15 per std. BLM instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

16			15		
Drove 5/8" x 3' rerod w/RLS cap (buried 0.5)			Set 5/8" x 36" rerod w/RLS cap (buried 0.5) & ced. post w/Loc tag.		
5" Maple	N25°W	45.5	3" W. Pine	S35°E	19.1
10" Maple	N55°E	56.2	6" W. Pine	S65°W	19.8
8" W. Pine	S28°E	48.1	Ctr. line E-W trail rd.	N	13'±
Cor. falls on S. Edge E-W trail rd.					
Set cedar post w/loc. tag N 16.5'					

SIGNED BY Carl F. Roser 01-12-82 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

MELROSE TOWNSHIP
CHARLEVOIX COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET