LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 33 N. ●., R. 9 ●. W.	K-9
2. PROPERTY CONTROLLING IN SECTION 26	,T. 33 N. ●., R. 9 ●. W.	2
3. MISCELLANEOUS PROPERTY IN SECTION 26	,T. 33 N. ●., R. 9 ●. W.	::322.19'S. OF K-9 :::322.19'S OF COR. CODE 2
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on FEBRUARY 26, 19 86, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on FEBRUARY 26 19 86, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

::

DROVE 5/8" X 34" REROD W/RLS CAP & SET CEDAR POST W/LOC TAG.

28°	MAPLE	S45°E	5.4'
3"	MAPLE	N04°W	26.6'
5"	APPLE	N55°W	39.6'

:::

DROVE 5/8" X 34" REROD W/RLS CAP & SET CED. POST.

4"	CEDAR	N84°E	32.5'
4"	CEDAR	S25°E	12.8'
15"	HEMLOCK	S10°W	31.3'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-9 RECOVERED NE COR OF SEC.26 (FD 1 1/2" X 60" PIPE), AS CALLED FOR IN E.A. ROBINSON'S 1909 SUR. NOTE'S AND FITS HIS N.B.T., BEECH (NOW 26"), N37°E, 47.1': E.A.R. HAD E.K. ROBINSON'S 1887 COR NOTE'S ON FILE IN JURY ROOM AT CO. BLDG.;SEE NORWOOD BK., PG.19.

2 DROVE 5/8" X 34" RECORD FOR E 1/8 COR ON N LINE OF SEC. 26.

:: DROVE 5/8" X 34" REROD FOR SE COR OF NORTH 10 ACRES OF E1/2 OF NE 1/4 OF SEC.26. COR FALLS IN OLD N-S FN, B-W ON CED. POSTS, MOSTLY DOWN.

::: DROVE 5/8" X 34" REROD FOR SW COR OF NORTH 10 ACRES OF E 1/2 OF NE 1/4 OF SEC.26.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-9

FD 1 1/2" X 60" PIPE (LEANED OVER) & SET DNR MON & CED POST.

:: 26"	BEECH	N37°E	47.1
5"	APPLE	S50°W	41.5
27"	MAPLE	N85°W	75.7
4"	MAPLE	N26°W	49.5

2

DROVE 5/8" X 34" RE-ROD W/RLS CAP & SET CEDAR POST.

10"	MAPLE	S50°W	22.8'
6"	MAPLE	S75°W	26.9'
6"	CEDAR	N50°E	51.8'
10'	CREEK	NORTH	65 '

:: = E. A. ROBINSON 1909 WIT

SIGNED BY Carl F. Roser 03-26-86 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN — CARL F. ROSER — SEAL — LAND SURVEYOR — No. 12028 — REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

CHARLEVOIX COUNTY
NORWOOD TOWNSHIP

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1978

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET