LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in CHEROYGAN			
(County)	Located In:	Corner Code ##	
Public Land Survey	T 33N R 02N	C-11, D-11	
	T R T R		
	T R		
	T R		
	T		Davistas of Davido Champ & Eile Mumber
	T R T R		Register of Deeds Stamp & File Number
, ropony in occi.			
4. Lot No, Recorde	d Plat		A B C D E F G H 1 J K L M
5. Private Claims			2 - 6 - 5 - 4 - 3 - 2 - 1 - 1
			³┞ ╃╏╏┪ ╇┼┼┼┼┼┼
	41160	nr 10 86	4 7 4 8 4 10 4 11 12 12
I, <u>CARL T. KIISKILA</u> in a field survey on <u>AUGUST 12</u> , 19 96 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned of the survey o			
is liese 1 and 2 above were in conformance with regulations and rules therefore as required in the			
current manual of survey instructions of Management or by a decree of a Court of	of the United Stales Depar	tment of the interior, Bureau of Land	8 19 20 21 22 23 24
above were in conformance with the ru	tes of the Michigan Board (of Land Surveyors or by a Decree of a	9 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Court of Law; established, re-estable	lished, monumented, re-	monumented, recovered, tound as	10 _30 _29 _28 _27 _26 _25
expressed below: NOTE: Not more than 4 corners,	all in the same town &	nd range, may be recorded	11 + + + + + + + + + + + + + + + + + +
NOTE: Not more than 4 corners, on this certificate.	all III the same town a		12 31 32 33 34 35 36
		d/or subsequent restoration:	13
A. Description of original monum C-11	P-11	d/or subsequent restoration.	
(NO EVIDENCE OF G.L.D. CORNER, B AS CALLED OUT IN THE G.L.O. LINE BELON.)	NOTES; UNLESS NOTED IN	LTEN "B"	
B. Description of corner evidence	e found and/or method	applied in restoring or reestablish	ning corner:
C-11	D-11	-	
FOUND AND ACCEPTED A 1" BAR	FOUND AND ACCEPTED A 1.	/2° BAR	
FOR THE SW COR OF SEC. 29 AS	AS SET BY J.SCWHANDT ,		
WIT. BY J.SCHWANDT, P.S.	#26466, PER HIS CERTIF SURVEY RECORDED IN LIB		
#26466; PER HIS CERTIFICATE OF SURVEY RECORDED IN LIBER 601,	PAGE 383; FOR THE S1/4	COR. OF	
PAGE 303.	SEC. 29.		
C. Description of monument for	corner and accessories	established to perpetuate locating	ig the position of the corner:
C-11	D-11		See OF MICHOLA
FD 1° IRON BAR.	FD 1/2" IRON , SET 1 1	/4" PIPE	CARL
tFN. POST S53°N 38.42'	OVER.	41.40	KIISKILA
AR.R.TIE FN POST N45°H 36.83' S.BATE POST N65°E 37.68'	#18" MAPLE NBO°M #12" POPLAR S64°W	46.11	LAND X SURVEYOR
S.BATE POST N65°E 37.68° #FN POST S44°E 42.60°	\$12" APPLE SO6"E	28.58	No.
VI.W. VOZ.	FN. POST N46°E	20.46	33981
	#COR FN. POST \$32°E SET GREEN FN POST 0.5	19.73' 5' NORTH.	SEO JANA SURVEY
# = OLD WIT. BY J.SCHWANDT, PS	SET UNLER IN FUST VOL	y realistring	18 VIII
	t = OLD WIT. BY J.SCHI	HANDT, PS	
QO T	Kuskila	Date	3 · 28 - 97
Signed by	13981		M APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
Surveyor's Michigan License No.		FOR	M APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYURS, JAN. 29, 1975 REVISED MAY 14, 1975 REVISED JAN., 1983