## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CURNER	CODE NUMBER	
1. PUBLIC LAND SURVEY	T N. R	E. W		
2. PROPERTY CONTROLL- ING IN SECTION —	3, T34	w. 9, 16		
3. MISCELLANEOUS PROPERTY IN SECTION		1		
4. LOT NO, RI				
5. PRIVATE CLAIMS				DECIDIED OF DEEDS GRAND AND
				REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in re-established, monumented, a and rules therefore as required Bureau of Land Management and 5 above were, in a field su	n lines 1 and 2 above were-monumented, recovered in the current manual correct by a decree of a court rvey on	re, in a field survey of d or restored as exp of survey instructions of law. Furthermore , 19, four	ressed below and of the United Se, that the corne ad, recovered, res	of P.A. 74, Michigan P.A. of 1970, ary 20 , 1981, established, d in conformance with regulations States Department of the Interior, or points mentioned in lines 3, 4 stored, established or re-established tration for Land Surveyors or, by a
A. Description of original mo	nument and accessories a	nd/or subsequent res	storation;	,
B. Description of corner evide	ence found and/or metho	d applied in restoring	g or re-establishii	ng corner;
9 Found pipe at corn	er probably as est	tablished in D.	. Adams surv	ev 1971.
9 Found pipe at corn	er probably as est	tablished in D.	. Adams surv	ev 1971.
9 Found pipe at corn	er probably as est	tablished in D.	. Adams surv	ev 1971.
9 Found pipe at corn	er probably as est	tablished in D.	. Adams surv	ev 1971.
9 Found pipe at corn	er probably as est	tablished in D.	. Adams surv	ev 1971.
9 Found pipe at corn 16 Set corner by stan  C. Description of monument 1	er probably as est dard survey proced	tablished in D. dure for the su	Adams survented to the	ey 1971. f sections.
9 Found pipe at corn 16 Set corner by stand  C. Description of monument 1 9 Left 1" pipe w/collar	er probably as est dard survey proced for corner and accessories in place	tablished in D. dure for the su established to perpe Set 3/4" x	Adams survey be abdivision of the tuate locating the 16 30" pipe and	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stan  C. Description of monument 1	er probably as est dard survey proced for corner and accessories in place 5 ft.	tablished in D. dure for the su established to perpe Set 3/4" x	Adams survey be abdivision of the tuate locating the 16 30" pipe and	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stan  C. Description of monument 1  9  Left 1" pipe w/collar 7" cedar N46°W 13.0	er probably as est dard survey proced for corner and accessories in place 5 ft.	tablished in D. dure for the su	Adams survey be abdivision of the tuate locating the 16 30" pipe and	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stan  C. Description of monument 1  9  Left 1" pipe w/collar 7" cedar N46°W 13.0	er probably as est dard survey proced for corner and accessories in place 5 ft.	tablished in D. dure for the su established to perpe Set 3/4" x	Adams survey be abdivision of the tuate locating the 16 30" pipe and	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stan  C. Description of monument 1  9  Left 1" pipe w/collar 7" cedar N46°W 13.0	er probably as est dard survey proced for corner and accessories in place 5 ft.	tablished in D. dure for the su established to perpe Set 3/4" x	Adams survey be abdivision of the tuate locating the 16 30" pipe and	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stand  C. Description of monument 19  Left 1" pipe w/collar 7" cedar N46°W 13.0 5" Cedar S21°E 27.0	er probably as est dard survey proced for corner and accessories in place 5 ft. 0 ft.	established in D. dure for the su  established to perpe  Set 3/4" x 10" Cedar 7" Cedar	tuate locating the 16 30" pipe and N24°E 29.0 S61°E 23.5	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stan  C. Description of monument 1 9 Left 1" pipe w/collar 7" cedar N46°W 13.0	er probably as est dard survey proced for corner and accessories in place 5 ft. 0 ft.	established in D. dure for the st  established to perpe  Set 3/4" x 10" Cedar 7" Cedar	tuate locating the 16 30" pipe and N24°E 29.0 S61°E 23.5	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stand  C. Description of monument 19  Left 1" pipe w/collar 7" cedar N46°W 13.0 5" Cedar S21°E 27.0	er probably as estandard survey processories in place of t. Of t.	established in D. dure for the su  established to perpe  Set 3/4" x 10" Cedar 7" Cedar	tuate locating the 16 30" pipe and N24°E 29.0 S61°E 23.5	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stand  C. Description of monument 19  Left 1" pipe w/collar 7" cedar N46°W 13.0 5" Cedar S21°E 27.0	er probably as estandard survey processories in place of ft.  Of the survey processories in place of the survey processories in place of the survey processories of the survey processo	established in D. dure for the st  established to perpe  Set 3/4" x 10" Cedar 7" Cedar	tuate locating the 16 30" pipe and N24°E 29.0 S61°E 23.5	ey 1971. f sections. e position of the corner:
9 Found pipe at corn 16 Set corner by stand  C. Description of monument 19  Left 1" pipe w/collar 7" cedar N46°W 13.0 5" Cedar S21°E 27.0  SIGNED BY Limit	er probably as estates agencies:	established in D. dure for the st  established to perpe  Set 3/4" x 10" Cedar 7" Cedar	tuate locating the 16 30" pipe and N24°E 29.0 S61°E 23.5	e position of the corner:  d post. 0 ft. 5 Ft. LAND

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975
MAY PLACE SKETCH ON BACK OR ATTACHED SHEET