

MICHIGAN DEPARTMENT OF CONSERVATION FORESTRY DIVISION

LAND CORNER RECORD

T. 37 N.R.'s 24 and 25 W

	Delt a and Menominee	COUNTY
DESCRIPTION OF CORNER _	1/4 corner for sections T37N, R25W 1/6 T37N, R24W	
CORNER MONUMENT	l" iron pipe with 4" aluminum cap	
DATE MONUMENT PLACED AN	D WITNESSED 9/16/68, F. J. Brey	
WITHESSES TO CORNER	6" Cedar (1/4S) (NBT) N 37° E, 09% links	
6 T 37 N	8" Cedar (1/4S) (NBT) S 30° W, 07 links	
R 24 W	AND	
CIRCLE CORNER REGISTERED		

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

This corner was replaced from a scribe wood post set by M. McNabb in 1918 from original B.T. This B.T. has been chopped out and is down. Point of older wood post was found alongside scribed post. Blazed and squared trees near.

SURVEYOR'S SEAL

SIGNED Trank J. Snar DATE 11/22/68

REGISTERED LAND SURVEYOR

Frank J. Bray