

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY.....	T. <u>38</u> N. R. <u>24</u> E. W.	<u>J-5</u>
2. PROPERTY CONTROLLING IN SECTION <u>14</u>	T. <u>38</u> N. R. <u>24</u> E. W.	<u>3</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, **Frank J. Bray** do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on June 12, 1973 19___, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

J-5
Woodpost:
 Tamarack 6 N62°E 48 links
 Tamarack 6 S40°W 3 links

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-5
 This corner was set mid-point and on a line between section corners east and west.
3.
 This corner was set mid-point and on a line between section corner north and corner south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

All bearings are magnetic. J-5 1" iron pipe with 1/2" brass cap. 3. 1 1/2" pipe.


J-5
 8" B. Spruce (1/8) (NBT) S58°W 11.9'
 4" B. Spruce (1/8) (NBT) North 15.5'

3.
 3" B. Spruce (N 1/16) (BT) N88°E 6.4'
 5" B. Spruce (N 1/16) (BT) S45°W 6.0'

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
 APPROVED AND SIGNED BY:  DATE **July 3, 1973**
CHIEF OF SURVEY PARTY
FRANK J. BRAY
MICHIGAN STATE BOARD OF REGISTRATION FOR LAND SURVEYORS (SEAL)

13575

SURVEYOR'S MICHIGAN REGISTRATION NO. _____