JAMES 5 2000

Approved By Delta County
Land Survey Remonumentation

	Lanu Survey	Demonumenta	III I
	Peer Group	Under Act 345	Of
P.A	. Of 1990 On	Under Act 345	199 <i>9</i>

## SECTION

T		Requirement						_			· \	
For corners in				Ì			•					
DELTA	Located In:	Corner Cod	e#	-		-						
(County)				İ				,		ı		
1. Public Land Survey	T 39 N R 1	9 W J-13	SAME		ر تُدر ا	ت ۱۳۰۰	<u>.0 (</u>	04	<u>00</u>	111		
1.1 abilo Lana Garvey	T <u>38 N</u> R_1		CORNER		·	<u> 2:</u>	00_	COLCO	<	700		
	T <u>39 N</u> R_1	.9 W K-07			135	33	9		<u></u>	<u> </u>		
0 B	Ţ <u> </u>		·	-		70	خصطار	غر ہے	<u> </u>	4		
2. Property Controlling in Section	S TR_ S T R	<del></del>		٠,		127.5	200		.`,:			
3. Miscellaneous	S T R											
Property in Sec.	S TR_					Decicl	or of D	eeds S	tome	. e Cii	la Mui	mhar
		07 MH COD SEC	2/1			regisi	.e. 01 D	eeus c	rain	o a r ii	ie ivu	HIDE
4. Lot No, Reco	is [\$1/4 cor sec 35] K- orded Plat											
5. Private Claims	ordod r rat			<del></del>	A 1 F	В	C D	E F	G H	I	JK	( L
	· · · · · · · · · · · · · · · · · · ·				2	_	   5	4-	<u>                                     </u>	,	- 2	İ -
					3 -	$\perp$						
M.P. DAVIS	_, in a field surveyon _	NOVEMBER 19_	99_ do hereby s	tate that under	4		8	ا ا و	<u> </u>	<u> </u>	-11	 12
requirements of P.A. 74, Michig	gan P.A. of 1970, the corner	points mentioned	in lines 1 and 2	above were in	5 -							-
conformance with regulations an United States Department of the					6	 18	  17	16-		5	-14	13-
that the corner points mentione Board of Land Surveyors or b					7			$\perp \perp$				
recovered, found as expressed by		Law, established,	ic colabilita,	monumentes,	8	19	20-	  21	  2	2	-23—	24-
NOTE: Not more than 2 co	more oil in the same town	and range may h	no recorded		ا و			<del>  _ </del> _	-	-	_	
on this certificate.	inicis, as in the same town	allu lalige, illay i	e recorded		10	30	29-	28		7	-26	25
					11						$\bot$	
					12	_  —31—	32_	33		1	-35	36-
					13							
<ul> <li>A. Description of original m</li> </ul>												
-13 [S1/4 COR SEC 35] JOH NO RECORD EVIDENCE OF	N BURT, D.S1845-WOOD CORNER RECOVERY AND/O	POST (BEECH 09 R SUBSEQUENT MO	" NO3°E 20 LI NUMENTATION	NKS)(BEECH C	9º N7	1°W 42	LINKS					
-07 [NW COR SEC 24] A.MERR M.S.MCNABB-1912-FOUND T.O'BRIEN-1980-L.2 OF	TRON BOLT SET BY JOHN	CRAIG COUNTY SU	RVEYOR-GATE F	POST NE DIREC	CTION	33.5	CORNER	? FENCE	NE D FENCE	IRECT POST	rion 3 r n44	38.2′ E
NEIL HILL, M.D.O.T19	87-L.5 OF LCR'S PG. 308 W 40.37')(CHINESE ELM 89-L.6 OF LCR'S PG.159 S SHOWN AT L.5 PG. 308	6" N25"W 52.00' -REPLACED, INSI	)(FENCE POST	S40 U 43 28'	')							
B. Description of corner ev	vidence found and/or met	hod applied in re	storing or rees	tablishing cor	ner:			ھے	<u> </u>	. مها		
-13 [S1/4 COR SEC 35] NO C OCCUPATION LINES(FARM R/W FENCES). ACCEPTED OF THE POSITION OF THE	FENCES N & S) AND COU AS BEING THE BEST AVAI	NTY ROAD IMPROV	EMENTS (1/2 D	ISTANCE BETW	ENT VEEN N	& S	JAN P	E OF	M	CH	G.	Ł
					r		\$ (0)		Л. Р AVI		12	1
-07 [NW COR SEC 24] FOUND CORNER MONUMENT FROM B ACCEPTED EXISTING MONU POSITION OF THE ORIGIN	BT'S RECORDED AT 1.6 OF IMENT AS BEING THE BEST	LCR'S PG.159.				<	1	LAND	SUR\	EYOR		RATE OF THE PROPERTY OF THE PR
							N. C.	TERED	16926	o su		F
C. Description of monumen	at for corner and accesso	ries established t	o perpetuate k	ocating the po	sition	of the	corner	MA	**************************************	-	•	
-13 SET A 5/8" REBAR W/A	3-1/4" ALLIM CAP STAMPE	ח זה זה זאר כסג	NER POSITION.									
CEDAR 05" CE NO8°W S	EDAR 06" POWER POLE 572°W \$28°E 59.68' 48.80'	NOTE: FARM	FIELDS IN QUADRANTS 46.24'							•		
-07 REPLACED EXISTING RLS CHINESE ELM 08" N20"W 51.90'	DRILL HOLE IN LARGE S49"W	P STAMPED TO ID FIELD STONES 30°E 8.40'	SURVEY MONU	POSITION. MENT SIGN PO M51°E 27.06'	s							•
NOTE: BEARINGS TO REFEREN	NCE OBJECTS ARE MAGNETI	C-DISTANCES ARE	TO A NAIL W	_				, UNLES	S OTI	HERWI:	SE NO	TED.
Signed by M.+	! SAUIS		·	Date	2/2	# /9	19		·			
Surveyor's Michigan License	No. 16476							-				