

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____ N. S., R. _____ E. W.		_____
2. PROPERTY CONTROLL- 24 _____ T. 41 _____ N. R. 22 _____ E. W. ING IN SECTION		5, 6, 12,
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. S., R. _____ E. W.		_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, David B. Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 13, 1984, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- 5-Not previously Established N 1/16 Cor. on the NS 1/4 line of Sec. 24
- 6-Not previously Established NE 1/16 Cor. of Sec. 24 (Center of the NE 1/4)
- 12-Not previously Established S 1/16 Cor. on the NS 1/4 line of Sec. 24

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 5-Set M.P.O.L. between N 1/4 Corner and the center post of section 24
- 6-Set at the computed center of the NE 1/4 of section 24, By closed traverse
- 12-Set M.P.O.L. between the south 1/4 corner and the center post of section 24

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|------------------------|-------------------------|------------------------|
| All D.N.R. Monuments | | |
| 5-3" R. Pine S26E 6.1' | 6-4" R. Pine S34W 17.8' | 12-5" Cedar N41E 27.8' |
| 1" R. Pine N82W 6.1' | 6" R. Pine N49W 25.5' | 12" Cedar S47E 21.8' |
| 5" R. Pine N7E 11.9' | 8 R. Pine N63E 29.0' | 10" Cedar S16W 40.9' |
| 9" R. Pine N85E 11.8' | 5" R. Pine S84E 28.8' | 5" R. Maple N60W 18.4' |

SIGNED BY _____

David B. Babbitt

DATE _____

9-12-84

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES: