

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY _____	T. <u>42</u> N. <u>X</u> , R. <u>22</u> <u>2</u> W.	<u>M-7</u>	<b>DELTA Co</b>
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ N. _____ S., R. _____ E. _____ W.	_____	
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. _____ S., R. _____ E. _____ W.	_____	
4. LOT NO. _____, RECORDED PLAT _____		_____	
5. PRIVATE CLAIMS _____		_____	

REGISTER OF DEEDS STAMP AND FILING NUMBER \_\_\_\_\_

I, David B. Babbitt do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on December 7 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

**A. Description of original monument and accessories and/or subsequent restoration:**

S.E. Section corner  
 Wood stake - elm 17 - N28°W - 15.7 ft.; cedar - S31°E - 31.8 ft.

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

Found 4" x 4" squared scribed cedar stake as set by M. McNabb in 1913. He says "ID. by orig. B.T. and witness - reset stake."

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

1" pipe, 4" aluminum cap  
 21" elm S50°W - 24.70'; 5" elm - North - 33.20'; 9" cedar - S 68°E - 13.70'

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_ CHIEF OF SURVEY PARTY \_\_\_\_\_ DATE \_\_\_\_\_ (SEAL)

MICHIGAN REGISTERED LAND SURVEYOR