

DEC 1 2 1997

COMMISSION

EATON COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

97 DEC -2 AM 10: 30

For Corners in EATON	Located In:	Corner Code #	LINDA M REGIST EATON	TWITCHE ER OF DEEL COUNTY, MI	LL JS CH.
(county) Public Land Survey ENTER 1/4 CORNER SECTION 6 BELLEVUE TOWNSHIP ON TOWNSHIP LINE Property Controlling S in Section SECTION SURVEY IN SECTION SURVEY	T_1N_R_6W TR TR TR TR	B-2	LIBER Register of Deeds S	3 PAGE Stamp & Fil	869
	TR TR				
Brian Reynolds, in a field survey of P.A. 74, Michigan P.A. of 1970, the conformance with regulations and runstructions of the United States Dependence of a Court of Law and/or the vere in conformance with the rules of a Court of Law; established, re-est sexpressed below. NOTE: Not more than 2 corners, on this certificate.	on 31 JULY, 1997 do here the corner points mentioned these therefore as required in the corner points mention of the Michigan Board of Le stablished, monumented, re all in the same town and	by certify that under requirements I in lines 1 and 2 above were in the current manual of survey treau of Land Management or by oned in lines 3, 4, and 5 above and Surveyors or by a Decree te-monumented, recovered, found d range, may be recorded the sand/or subsequent restoration:	A B C D E F G 2	H J 3 2 10 11 15 14 1 22 23 27 26 1 34 35 35 1 1 1 1 1 1 1 1 1	12 12 13 14 15 15 15 15 15 15 15
	OF ACT BY THE G	ENERAL LAND OFFICE.		EECH 8 S4	3E 98
2. COUNTY SURVEYOR	RECORDS: OSCA	R CHURCH, 8 JUNE, 1878 (V	ATE AVAILABLE FOR T	HIS CORN	ER ***

- *** NO OTHER HISTORICAL INFORMATION, PUBLIC OR PRIVATE, AVAILABLE FOR THIS CORNER ***
- 3. Description of corner evidence found and/or method applied in restoring or reestablishing corner: OUND NO MAGNETIC EVIDENCE OF CORNER MONUMENTATION. TRAVERSED OF ALL OF SECTION 6, TYING IN OLD OCCUPATION FENCE AND TREE LINES THROUGHOUT SECTION. FOUND FENCE CORNER POST SURROUNDED 3Y STONES AT B-2 TO FIT VERY WELL WITH NORTH-SOUTH & EAST-WEST 1/4 LINE OCCUPATION. EXCAVATION AROUND FENCE CORNER REVEALED NOTHING.

ACCEPTED EAST-NORTHEAST SIDE OF FENCE CORNER AS BEST AVAILABLE EVIDENCE OF CORNER POSITION. BET STANDARD EATON COUNTY REMONUMENTATION MONUMENT ON THE EAST-NORTHEAST SIDE OF FOUND ENCE CORNER POST, IN PIT OF STONES.

> Description of monument for corner and accessories established to perpetuate locating the position of the corner.

BET STANDARD EATON COUNTY REMONUMENTATION MONUMENT (3/4" X 36" IRON) WITH PLASTIC CAP. SET 20d NAIL W/PLASTIC TAG IN THE SOUTHEAST CORNER OF A RAILROAD TIE FENCE CORNER POST

(LEANING WEST-SOUTHWEST) S05°W 1.12'

SET 20d NAIL WIPLASTIC TAG IN THE NORTHWEST SIDE OF AN 8" CHERRY N52°E 1.77"

BET 20d NAIL WIPLASTIC TAG IN THE WEST SIDE OF A 10" CHERRY S02°E 19.16" SET 20d NAIL W/PLASTIC TAG IN THE NORTHEAST SIDE OF AN 8" CHERRY S31°E 10.64"

SET 20d NAIL WIPLASTIC TAG IN THE SOUTHEAST SIDE OF A 10" WHITE OAK S34°W 10.30"

CORNER IS 0.6' EAST & 0.4' NORTH OF FENCE CORNER POST (LEANING WEST-SOUTHWEST)

N LINE WITH DECAYING FENCES NORTH-SOUTH (MOSTLY DOWN)

1-2 LIES N89°13'42"W 2859.17'

3-1 LIES N00°35'13"E 2764.65'

3-2 LIES S89°13'42"E 2654.04"

3-3 LIES S00°35'13"W 2650.75'

P.A. 345 EATON COUNTY PEER APPROVED 9/18/97

MIEH BRIAN REYNOLDS CAND SURVEYOR NO. 31602 DLAND

signed by Su		
Signed by \	nse No316	02