DEC 08 1993

LAND CORNER RECORDATION CERTIFICATE

COMMISSION For corners in	Filing Require	ement of Act 74, Mich. P.A. 1	970 93 DEC -2 PN 3: 27
EATON [County]	Located In:	Corner Code ##	LINDA M. TWITCHELL REGISTER OF DEEDS EATON COUNTY, MICH.
1. Public Pand Sunsy IP	T 4M_R 3W_ TR TR TR	G_6	
in Section S	T R T R T R		Register of Deeds Stamp & File Number
			negister of beeds stamp a rile number
4. Lot No, Recorded	i Plat		АВС D E F G H I J K L M
5. Private Claims IR.WSteadman , in a field of hereby certify that under requirement in tines 1 and 2 above were in conform current manual of survey instructions of Management or by a decree of a Court of above were in conformance with the rule Court of Law: established, re-established expressed below: NOTE: Not more than 4 corners, a on this certificate.	eld survey onOCt. sof P.A. 74, Michigan P.A. of ance with regulations and the United States Departr Lawand/or that the corner es of the Michigan Board of shed, monumented, re-mall in the same town and	ober 30 , 19 93 , of 1970, the corner points mentioned if rules therefore as required in the ment of the Interior, Bureau of Land points mentioned in lines 3, 4 and 5 Land Surveyors or by a Decree of a onumented, recovered, found as drange, may be recorded	2 6 5 4 3 2 1 3 4 7 8 9 10 11 12 5 6 18 17 16 0 15 14 13 7 7 8 19 20 21 22 23 24 9 10 30 29 28 27 26 25 11 12 31 32 33 34 35 36 13
A. Description of original monume	nt and accessories and/	or subsequent restoration:	

1. Original Post set by Musgrove Evans D.S. in Feb. 1827 Beech 9" N68°E 25 Ironwood 5"-N75½°W-20

2. Field Notes in the back of the Eaton County Road Commission (ECRC) Copy of the GLO Notes Maple N45E 58

(OVER)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Searched apparent area of corner and found 3/4" Pipe in Mon. box. Excavated Bottom of monument box and found that pipe was imbedded in concrete. Pulled pipe (after much labor) and probed resultant hole to a depth of 4 feet and found nothing more. Proved corner location by using the remains of Harvey Williams Oak Anchor post witness (S18°E 72.3') All of N.C. Jones witnesses and Clyde Stephens 38"Oak and House #110 witness. The remains of Williams Oak Anchor post and the remains of Jones steel end post are in the same fence line on the South line of an abandoned railroad right-of-way and both match the location of the corner. Set Standard Bar and Cap in place of pipe.

Field work conducted by Dave Clifford PS#25837

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Standard $3/4" \times 24"$ Eaton County Remonumentation Bar and PA 345 Cap PS#11370.

Set Nail & Tag #11370 in N.E. side 17" Basswood Az 134° 89.40'

Gas Marker

Az 158° 70.75' Az 204° 74.98'

MDSH Tag in E. Side Util Pole Set Nail & Tag #11370 in E. Side 42" Oak

Az 333° 149.00'

Date _

S.E. Corner foundation house # 110

Az 83° 124.65'

OF MICHARD W SURVE NO. 11370
11370
AND SUR

November 22, 1993

_11370 Surveyor's Michigan License No. ___

P.A. 345 EATON COUNTY, FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYCRS, JAN. 28, 19 REVISED MAY 14, 19 23/93 120

PEER APPROVED ..

- 3. Marginal Note in the ECRC Copy of the GLO notes by Harvey Williams County Surveyor Anc. Post N89°W 33½' Oak Anc. Post S18°E 72.3'
- 4. ECRC Grid Map.
 Anc. Post W. 33.5'
 Oak Anc. Post SSE 72.3'
 40" Oak N.W. 148.85'
 P.P. S.W. 74.35'
 18" Cherry S.E. 83.75'
- 5. N.C. Jones LS#2934 recorded corner in Dec. 1971 in Liber 1 of Corners page 70 with C.E. Smith as party chief for MDSH as a found railroad spike fitting all property descriptions in area. Placed 3/4" Pipe in monument box. 8" Box Elder S35°E 89.38' P. Pole S20°W 75.04' Steel End Post S18°E 70.8'
- 6. Clyde Stephens LS #3829 recorded corner in Dec. 1971 in Liber 1 of Corners page 87 as a found 3/4" Pipe in Mon. box.
 Tag in 38" Oak N34°29'W 148.85'
 Tag in 14" Cherry S35°16'E 83.86'
 S.W. Corner 1 sty House #110 N80°E 124.65'
- 7. Ron Helsel LS#18994 used corner in a survey in May 1974 recorded in Liber 1 o Surveys page 692 with a reference to Liber 1 of corners page 87 and used again in a survey in Jan. 1980 recorded in Liber 3 of Surveys page 77 with a reference to Liber 1 of Corners page 87
- 8. Dave Lohr LS#30090 used Corner in a Survey in July 1989 recorded in Liber 3 of Surveys page 979 with a reference to Liber 1 of Corners page 87
- 9. Doug Richardson #31603 used corner in a survey in Nov 1989 recorded in Liber 4 of Surveys page 718 with a reference to Liber 1 of Corners page 87.