

MAY 0 5 1997

Surveyor's Michigan License No._

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

96 DEC 31 PH 2: 26

For corner	re în	Filing Requirement of Act 74, Mich. P.A. 1		. 111 21 26
roi come	15 HI		A.	Erne C. Sien
EMME	Τ	Located In: Corner Code #	7-0-0	white with the
	(County)	TOWNSHIP	Kt (RISTER OF OFFICE
1. Public	Land Surve	T		A A
	ECRP#124	T R		PAGE 155
2. Proper in Sec 3. Miscel		TR		
	ty in Sec.	S T R	Register of	Deeds Stamp & File Num
•	•		negister of	Deeds Statilp & File Num
4 Lot No		December of Dist		₩,
5. Private	Claims	Recorded Plat	A B C D	EFGHIJK
			2 6 5	
			3	3 2
I Richard	i F Oelka	in a field surroy on 20 December 40.00		
under requir	rements of P.A	in a field survey on <u>20 December</u> , 19 <u>96</u> do hereby certify that . 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2	5 7 8-	9 10 11
above were	in conforman	se with regulations and rules therefore as required in the current manual of	-	
by a decree	uctions of the e of a Court of	United States Department of the Interior, Bureau of Land Management or Law and /or that the corner points mentioned in lines 3, 4 and 5 above	6 18 17	16 15 14
were in cor	nformance wit	n the rules of the Michigan Board of Land Surveyors or by a Decree of a	7	
Court of L expressed b	aw; establish	ed, re-established, monumented, re-monumented, recovered, found as	8 19 20	21 22 23
cxpressed a	ocion.		9	
NOTE: No	ot more that	4 comers, all in the same town and range, may be recorded	10 30 29	28-27-26-
on	this certificat	te.	11	
			12 31 32	33 34 35
A. Descri	iption of orig	inal monument and accessories and/or subsequent restoration:	13	
C-5co	orner comm	on to Sections 7, 8, 17, &18, T34N, R5W		
See Outiin	ne of Corne	r History on back.		
This corne	er was lisan	extensively at the turn of the contain.		
large iron	pipe was fi	l extensively at the turn of the century. It was probably lost rst found in 1971 set by persons unknown and has been utili	when Howard	Rd. was upgraded A
	leden man	to to the set by persons unknown and has been unin	zea since. APP	ROVED LAND CORNER
				P.A. 345 OF 1990
			1	Emmet County
B. Descrip	tion of corner	evidence found and/or method applied in restoring or reestablishing corner:	***************************************	12.30.96
		on to Sections 7, 8, 17, &18, T34N, R5W	ند	AND THE PROPERTY OF THE PARTY O
Found 1-1	/4" iron pip	e, 1' long, in centerline of Howard Rd. in lange cut.	A CONTRACTOR OF THE PARTY OF TH	E DE MICH CHARLES
No 40=		SSED AS FOLLOWS:		RICHARD E 🔪 💃 📜
N24°E		10" maple, nail capped PS# 31601 in NW face	! =/ ,	OELKE 5
N24°E N57°E		10" maple, spike in SE face	2 5 − 5	ROFESSIONAL SURVEYOR
N87°E		6" basswood clump, nail capped PS# 31601 in S face 2" pipe	1.5	No.
S89°E		T-iron, capped PS# 15401	10 7	33983
S89°W		T-iron, capped PS# 15401	The state of the s	011310
				Carallet St. St. St. Com.
C. Description	on of monume	nt for corner and accessories established to perpetuate locating the position	of the corner	•
C-3CD	rner commo	in to Sections 7, 8, 17, &18, T34N, R5W		
Replaced 1	/-14/" iron	pipe with a 2" diameter, 30" long PVC pipe, with a base may	gnet and a stan	darad Emmet County
corner.	monumenta	tion Program cap. This position is accepted as a careful and	faithful perpetu	uation of the original
COLLIE!		TNESSES:		
S18°E		o.p., nail capped PS# 33983 in NE face		
S29°W	64.61'	3" elm, nail capped PS# 33983 in W face		
N23°W		3"elm, nail capped PS# 33983 in E face	•	

DAGE 156

EMMET COUNTY REMONUMENTATION PROGRAM CORNER NO. 124

34-5-C5 T34N R5W Section cor. bet. 7/8/17/18 LEARS ROAD

Date	Surveyor	Found	Witnesses	Notes
1840	GLO	Set post.	1) S. 37°E. 40L 24" Hemlock 2) S. 65°W. 22L 24" Hemlock	
187? 1881 1884 1885 1885	Keep Keep Keep Keep Keep	ran S/L sec. 7 ran S/L sec. 7 ran E/L sec. 7 ran S/L sec. 7 ran S/L sec. 8 ran E1/2 S/L s	7, fd cor. ? 7, fd cor. ? 7, fd cor. ?	
1894	Main	ran N/L sec. 1	.8, fd stone, and witnessed.	
1957	G. Young?	Survey for Wil	helm, found no evidence of cor.	
1971	Schweigert & Young		ner Section 7, found 1 1/2" pipe (Field Notes).	e in
1979	Green	1) 2) 3)	fd. 1" pipe at road surface. N26°E 60.08' 8" Maple N58°E 32.59' 4" Maple West 33.0' "t-iron" N68°W 35.26' p.p.	
1979-86	6 Green		lyde),(City of Petoskey),(McLaugh), (Swadling), fd cor. as noted.	
1980	J. Young	1) 2)	ers, found 1" pipe N27°E 60.10' 7" Maple N59°E 32.61' 4" Maple N66°W 35.20' p.p.	
1987	Bidstrup & Young	Survey for Tit Section 18.	le Insurance Co. of Minn., Found	N.E. corner of
1992-94	4 Swenor	Field notes, f	ound 1 3/4" pipe.	
1992-94	4 Trowbridge		immerman), and (McIntosh), found ipeas witnessed in (L2 P31)	N.W. corner Section