LAND CORNER RECORDATION CERTIFICATE

· · · · · · · · / · · · / · ·

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF -: | | 1 | |
|---|--|---|---|
| 1. PUBLIC LAND SURVEY | T. 37 K. 4 | H-10 | |
| 2. PROPERTY CONTROLL- 2 ING IN SECTION- | 7 ,T 37 N. R. 4 | 5 | |
| 3. MISCELLANEOUS PROPERTY IN SECTION — | | | • |
| 4. LOT NO, RE | | | |
| 5. PRIVATE CLAIMS | | | REGISTER OF DEEDS STAM |
| Kenneth J. Ost | ling de Leeshee | and the short of the second | nents of P.A. 74, Michigan P.A. |
| the corner points mentioned in re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field sur | lines 1 and 2 above were, in 2-monumented, recovered or in the current manual of sur or by a decree of a court of la- vey on | a field survey onQctc restored as expressed belowey instructions of the Un w. Furthermore, that the _, 19, found, recovers | ober 24, 1979, 19 , estable and in conformance with regulated States Department of the corner points mentioned in lired, restored, established or re-est Registration for Land Surveyors |
| A. Description of original mor | nument and accessories and or | r subsequent restoration: | |
| | | • | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| Set corner at calcu | nce found and/or method appointed intersection of the subdivision of | f true ¼ lines acc | |
| Set corner at calcusurvey procedures for Set by standard sur | plated intersection of or the subdivision of the subdivision of the control of th | f true 4 lines acc f sections. e subdivision of s | ording to standard |
| Set corner at calcusurvey procedures for Set by standard sur | plated intersection of or the subdivision of every procedure for the or corner and accessories established | f true 4 lines acc f sections. e subdivision of s | ording to standard ections. |
| survey procedures for Set by standard survey. C. Description of monument for | plated intersection of the subdivision of the subdi | f true 4 lines acc f sections. e subdivision of s | ording to standard ections. ing the position of the corner: |
| Set corner at calcusurvey procedures for Set by standard sur C. Description of monument for Set 5/8" Report Nail in 12 | plated intersection of or the subdivision of every procedure for the or corner and accessories established | of true 4 lines according for sections. e subdivision of subdished to perpetuate locations. Set 5/8" Rod .0 4" W. Pine | ording to standard ections. ing the position of the corner: 5 & Red-Top Post N73 ^o E 11.82 |
| Set corner at calcusurvey procedures for Set by standard sur C. Description of monument for Set 5/8" Report Nail in 12 | plated intersection of the subdivision of the subdivision of the subdivision of the corner and accessories established with the corner and accessories accessories and accessories accessories accessories accessories and accessories | of true 4 lines according for sections. e subdivision of subdished to perpetuate locations. Set 5/8" Rod .0 4" W. Pine | ording to standard ections. ing the position of the corner: 5 & Red-Top Post N73 ^o E 11.82 |
| Set corner at calcusurvey procedures for Set by standard sure. C. Description of monument for Set 5/8" Report Nail in 12 Nial in 4 | plated intersection of for the subdivision of every procedure for the or corner and accessories established w/RLS Cap "J. Pine N65°E 32" "J. Pine N04°E 28 | of true 4 lines according sections. e subdivision of subdivision | ording to standard ections. ing the position of the corner: 5 & Red-Top Post N73 ^o E 11.82 |
| Set corner at calcusurvey procedures for Set by standard sur C. Description of monument for Set 5/8" Report Nail in 12 | related intersection of for the subdivision of every procedure for the procedure for the for corner and accessories established with the subdivision of the subdivisi | of true 4 lines accord sections. e subdivision of | ording to standard ections. ing the position of the corner: \$ Red-Top Post N73°E 11.82 S10°E 29.0 KENNEY: |
| Set corner at calcusurvey procedures for Set by standard sure. C. Description of monument for Set 5/8" Result in 12 Nial in 4 | or the subdivision of the subdiv | of true 4 lines accord sections. e subdivision of | ording to standard ections. ing the position of the corner: \$ Red-Top Post N73°E 11.82 S10°E 29.0 KENNEY: |
| Set corner at calcusurvey procedures if Set by standard sur C. Description of monument for Set 5/8" R Nail in 12 Nial in 4 SIGNED BY Exercic | TATES AGENCIES: | of true 4 lines accord sections. e subdivision of subdished to perpetuate located Set 5/8" Rod .0 4" W. Pine .81 6" J. Pine | ording to standard ections. ing the position of the corner: \$ Red-Top Post N73°E 11.82 S10°E 29.0 KENNET: 1.00 |

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1973
MAY PLACE SKETCH ON BACK OR ATTACHED SHEET