ENG DIVISION

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 37 N., R. 5 W.	M-5; L-5; L-7; K-6
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MARCH 17, 19 83, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

L-7
FOUND 5/8" ROD W/CAP RLS #11360
* (FOUND WITNESSES)
* NAIL IN 36" S. MAPLE N42°W 92.0'
* NAIL IN FENCE CORNER POST N7°E 35.03'

K-6
LEFT 1/2" IRON BOLT IN PLACE
12" R. MAPLE N80°W 35.2'
10" R. MAPLE S49°W 50.0'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-5 - SET CORNER RELATIVE TO STREAM TIES SOUTH AND WEST, WHICH ALSO CONFORMS TO PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS NORTH AND SOUTH. ONLY LOCATION THAT WOULD FIT SMALL STREAMS AND STILL MAKE REASONABLE N-S MEASUREMENT.
L-5 - SET BY PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNER.
L-7 - FOUND ROD AND CAP IN PLACE BY PREVIOUS SURVEY.
K-6 - FOUND BOLT IN PLACE IN ℄ ROAD FROM PREVIOUS SURVEY BY UNKNOWN.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-5
SET DNR MONUMENT & CEDAR POST
6" HEMLOCK N2°W 12.5'
9" CEDAR S75°W 22.6'

L-5
SET DNR MONUMENT & CEDAR POST
4" S. MAPLE N41°E 25.0'
6" S. MAPLE S73°E 4.0'
SET 4" CEDAR POST BY CORNER

SIGNED BY Kenneth J Ostling DATE 10/1/83

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR NO. 10068 REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ EMMET COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET