

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>22</u> T. <u>5</u> N. R. <u>6</u> E.		<u>7-8</u>
2. PROPERTY CONTROLLING IN SECTION <u>22</u> T. <u>5</u> N. R. <u>6</u> E.		<u>7-8</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. R. _____ E.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

Genessee Co

I, Dwayne Scott do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram-over) were, in a field survey on Dec. 23 1971, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on December 23 1971, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Found 1/2" Iron Pipe Placed Cap on Pipe

Witnessed furnished by Delta Eng. of Flint, Michigan
N40°W 34.0 Power Pole
Right Angle 99.75 off W. Edge of South Bound Lane 45-23
Measurement Ex. P.C.C.S.W.P.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1/2" I.P. with Cap # 12029

<u>N 38° W</u>	<u>11.7'</u>	<u>3" Scotch Pine</u>
<u>West</u>	<u>20.8'</u>	<u>R.O.W. Fence</u>
<u>S. 05° E.</u>	<u>36.3'</u>	<u>4" Scotch Pine</u>
<u>N. 40° W.</u>	<u>34.0'</u>	<u>Power Pole</u>
<u>S. 46°</u>	<u>19.8'</u>	<u>N. Sign Post of</u>

FENTON CITY LIMITS

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ CHIEF OF SURVEY PARTY DATE _____

APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR DATE _____ (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____