SURVEY & REMONUMENTATION	ON 🔿			***
MAR 2 3 2000		Mil Part	12.	
* GILBERT G. * SECTION  * BONNO * LAND CORNER RECORDATION	CERTIFICATE			
PROFESSIONAL SURVEYOR 5 Filing Requirement of Act 74, M				
For corners in 32332	R	CELESEE COM	TY TOS	
Genesee Located In: Gaines Township Corner Code # G-2	NASTER LIBER	4355 PAGE	64	
1. Public Land Survey T6N R5E	1	·	これののちつ	,
T	filed & Register o	ALC // Co	le Number	
3. Miscellaneous S T R Property in Sec. S T R	L			
4. Lot No, Recorded Plat 5. Private Claims	1 ' 2 3	A B C D E F	6 H I J	K L
	4	7 8 9	10-11	12
I, <u>Gilbert G. Bonno, P.S.</u> , in a field survey on <u>November 17</u> do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner poin lines 1 and 2 above were in conformance with regulations and rules therefore as it	required in the 6	18 17 16	15 14	18
current manual of survey instructions of the United States Department of the Interior, Bu Management or by a decree of a Court of Law and/or that the corner points mentioned in li above were in conformance with the rules of the Michigan Board of Land Surveyors or by Court of Law; established, re-established, monumented, re-monumented, recovery	ines 3, 4 and 5 'y a Decree of a 8	19 20 21	22 23	24
expressed below:	10	30 29 28	27 26	25

#### A. Description of original monument and accessories and/or subsequent restoration:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this 11

1823, GLO by John Mullet, D.S., wood post, 2 accessories listed, G-2 to G-1 = 43.60 ch (2877.6'); G-3 to G-2 = 40 ch. 2640 (1878, Genesee County Surveyor Records (Large Book) Page 40 by Stephen Mathewson, C.S., None given, G-2 to G-1 = 43.57 ch (2875.62')

12

31

32

33

1878, Genesee County Records (Large Book) Page 40 by William B. Sears, D.C.S., Hub and Stone, G-2 to G-1 = 43.49 ch (2870.34'); G-2 to F-2 = 39.76 ch (2624.16'); G-2 to G-3 = 39.78 ch (2625.65')

1920, GCRC field notes and drawing #1119, Stone, G-2 to G-1 = 2891.80'

1978, ROWE witness card, None given, 3 accessories listed, none exist.

1980, Act 132 by Elbex B. Harris #9431 recorded on L.2091, P.419, "T" iron and stone, 5 accessories listed, one exists ir 1999, S45W, 47.52' nail/Gould tag in 12" ash.

(Cont'd on back)

certificate.

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

·1999 REMON - Found "T" iron w/rocks stacked around

In the 1823 GLO survey by John Mullet, D.S., a wood post is indicated as the corner with one measurement G-2 to G-1, 43.57 ch (2875.62 feet). Two accessories noted neither of which exist in 1999. In the 1878 Genesee County Survey by Stephen Mathewson, C.S., one measurement was given G-2 to G-1, 43.57 ch (2875.62 feet). In the 1878 Genesee County survey by William B. Sears, D.C.S., a hub and stone are indicated as the corner with three measurements, G-2 to G-1, 43.49 ch (2870.34 feet); G-2 to F-2, 39.76 ch (2624.16 feet) and G-2 to G-3, 39.78 ch (2625.65 feet). One accessory indicated; not found in 1999. In the 1920 Genesee County Road Commission drawing #1119, a stone was indicated as the corner with one measurement G-2 to G-1, 2891.80 feet. In the 1980 Act 132, Liber 2091, Page 419f, by Elbex B. Harris, a "T" iron next to stone was indicated as the corner. Five accessories are noted, one of which exists in 1999 and compares within 0.06 of record. In the 1995 Act 132 by Gilbert Bonno, a "T" iron was indicated as the corner. Six accessories are noted, four of which exist in 1999 and compare within 0.05 to 0.40 of record. In January 25, 1996, field notes from Cornerstone Engineering and Surveying indicated a "T" iron as the corner. The same six accessories as the 1995 survey being noted with same four being found in 1999 and compare within 0.05 to 0.40 of record. (Cont'd on back)

#### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

S45°W 47.52' Fnd nail/tag in 8" Ash (47.46' M)
N31°W 55.62' Fnd nail/tag #32332 in 10" Ash (55.56' M)
West 29.58' Fnd nail/tag #32332 in 6" Ash (29.53' M)
S60°W 28.15' Fnd nail/tag #32332 in 6" Ash (28.08' M)
N65°E 59.93' Fnd nail/Gould tag in S. face 6" Ash

\$80°E 58.09' Fnd nail/Gould tag in N. face 12" Ash

I set the Standard Bernsten Monument SS-A-5-BR-30 (3 1/4" D. Brass cap Stamped "Genesee County Remonumentation Corner 32332, 1999") with 30" x 23/8" O.D. Stainless Steel tube with plastic base.

Ratified by the Genesee County Peer Group December 15, 1999.

Signed by Mulleut 4. Bornso Surveyor's Michigan License No. 32332

Date 12-15/99

35

3ć

34

SURVEY & REMONUMENTATION

MAR 23 2000

SECTION

### A. Description of original monument and accessories and/or subsequent restoration (Continued):

1980, Act 74 by Elbex B. Harris #9431 recorded on L.2091, P.418, "T" iron next to stone, 5 accessories listed, 1 exists., S45W 47.52' nail/tag in 8" Ash

1995, Act 132 by Gilbert G. Bonno #32332 as found in F11369, "T" iron, 6 accessories listed, 4 exist and check well 1/25/96, Field notes by Cornerstone Engineering and Surveying, "T" iron, 6 accessories listed, 4 exist and check well 1/30/96, Act 132 by Gilbert Bonno, revised 2/16/99 "T" iron, 4 accessories listed and found; all check well.

# B. Description of corner evidence found and/or method applied in restoring or reestablishing corner (Continued):

In January 30, 1996, Act 132 revised in 1999 by Gilbert G. Bonno, a "T" iron was indicated as the corner with four accessories noted, all four being found and comparing within 0.00 to 0.03 of record.

Today in the 1999 remonumentation program, I am finding a "T" iron with rocks stacked around it. A tree line runs to the west. Excavated down and found no signs of additional monumentation. I accept this corner as the best available evidence of the position of the original corner.

Ratified by Peer Group in accordance with P.A. 345, 1990
Co. Rep Alexander Co. Rep A