

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

GENESEEE (County)	Located In:	Corner Code #/1
1. Public Land Survey	T 6N R 6E	F-5
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

20115  
9.00  
Register of Deeds Stamp & File Number

APR 4 2015  
RECORDED  
FILED

- 4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
- 5. Private Claims \_\_\_\_\_

I, RICHARD H. KRAFT, in a field survey on, DECEMBER, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	18	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- HARVEY PARKE - GLO -1823- SET CORNER-NO ACCESSORIES
- 1973 F. SHALTZ - FOUND RAILROAD SPIKE - 3 ACCESSORIES
- 1993 FLINT SURVEY & ENGINEERING-FOUND RAILROAD SPIKE - 4 ACCESSORIES
- 1995 RICHARD H. KRAFT - FOUND IRON

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 1995 GENESSEE COUNTY REMONUMENTATION PROGRAM
- 1973 - FOUND TWO ACCESSORIES
- 1993 - FOUND THREE ACCESSORIES

Ratified by Peer Group in accordance with P.A. 345, 1990

Co. Rep. Carl Carlson  
Date 12-20-95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- SET STANDARD GENESSEE COUNTY MOUMENT IN MONUMENT BOX
- CARLSON TAG IN POWER POLE, N45°E, 57.8' FT.
- GC TAG IN 4" TREE, S10°E, 35.55' FT.
- DELTA TAG IN POWER POLE, SOUTH 33.85' FT.
- CENTER-MANHOLE RIM S55° W, 65.45' FT.

SURVEY & REMONUMENTATION

MAY 31 2000

SECTION

Signed by Richard H. Kraft  
Surveyor's Michigan License No. 10064

Date 12-23-95