STATE OF MICHIGAN DEPARTMENT OF NATURAL RESOURCES

LAND CORNER RECORD

		Gogebic COUNTY
		T47N R42W
DESCRIPTION OF CORNER _	East 1/16 corner between Sec	tions 20 and 29
CORNER MONUMENT _ 1" I.D	. x 36" iron pipe with 4" alum	inum cap
DATE MONUMENT PLACED AND WITNESSED July 13, 1971		
WITNESSES TO CORNER	White Ash 6 S89°W (mag.)	10.1 ft. "1/16S, BT"
N	Sugar Maple 6 S61°E (mag.)	10.2 ft. "1/16S, BT"
20	AND	
CIRCLE CORNER REGISTERE	D	

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

No evidence that the corner had been established previously. Corner established on line between section corner 1329.2 ft. E and 1/4 corner 1329.2 ft. W.

SURVEYOR'S SEAL

SIGNED

REGISTERED LAND SURVEYOR
Arthur O. Enger

DATF June 20, 1972

DISTRIBUTION:

County Courthouse Area Forester (Regions I & II) District or Region Surveyor Forestry Div., Lansing

R 4047 Rev. 10/68