

STATE OF MICHIGAN
DEPARTMENT
OF
NATURAL RESOURCES

LAND CORNER RECORD


Gogebic COUNTY
T 47N R 42W

DESCRIPTION OF CORNER 1/4 corner between Sections 21 and 28

CORNER MONUMENT 1" I.D. x 36" iron pipe with 4" aluminum cap

DATE MONUMENT PLACED AND WITNESSED July 15, 1971

WITNESSES TO CORNER..... Sugar Maple 6 N41^oE (mag.) 22.4 ft. "1/4S, NBT"



Hemlock 11 S12^oE (mag.) 9.1 ft. "1/4S, NBT"

Sugar Maple 10 S32^oW (mag.) 18.7 ft. "1/4S, NBT"

AND

CIRCLE CORNER REGISTERED

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

Found a 10" maple blazed on 4 sides S32^oW 19 ft. for an approximate corner.

Corner re-established proportionately on line between section corner 2656.4 ft. W and meander corner 1908.5 ft. E. 1.55 ch. E to stream 3 lka wide course N, exactly as recorded in original field notes.

SURVEYOR'S SEAL

DISTRIBUTION:

SIGNED

Arthur O. Enger
REGISTERED LAND SURVEYOR
Arthur O. Enger

DATE

June 21, 1972

County Courthouse
Area Forester (Regions I & II)
District or Region Surveyor
Forestry Div., Lansing

R 4047
Rev. 10/68