MAR 0.2 2000

MAR 0.2 2000		ETIEICATE Register's vilice sa.
	LAND CORNER RECORDATION CE Filing Requirement of Act 74, Mich.	3 () 11 () () () () () () () ()
SECTION		21 ST day of July
For corners in Gogebic Located In:	Corner Code #	A. B. 19 99 at 1:25 s'clock P. m., and recorded in
1. Public Land Survey Section T	31 R 48N 46W C-11	Pamera Callina Deputer
2. Property Controlling S To Section S To S To S To S To Section S	R	Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat		1 A B C D E F G H I J K L M 2 5 5 4 3 2 1 1
I John R. Garskein a field requirements of P.A. 74, Michigan P.A. of 197 conformance with regulations and rules therefor United States Department of the Interior, Burea that the corner points mentioned in lines 3, 4 a Board of Land Surveyors or by a Decree of provided found as expressed below:	survey on May 12, 1999 do hereby state of the corner points mentioned in lines 1 and 2 above were in conformance with the rules of the account of Law; established, re-established, re-establi	ove were in ctions of the Law and /or 6 19 17 16 15 14 13
Original Township Su	nd accessories and/or subsequent restoration arvey by William & John Burt, 18 Survey by Austin Burt, D.S. 1851 ver - Set post 55 links south of co 18 links 15 links	
I found no original of existing surveys and	the 1/4 corner to 31 and 32, through oints found from a 1977, George Voted corner position falls in Black	reestablished the witness corner using petween sections 31 and 32. I extended the monumented north 1/16th corner vilson Survey and the Plat of Viking River as does the original witness FER CROUP APPROVED L. Dram 1/20/99

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner;

I set a W.C./M.C. to the original witness corner as shown on the sketch on back, 72.65' south of the original witness corner location. I set a 3/4" diam. x 3 ft. long alum. rod with 3 1/4"

alum. cap stamped to identify the corner, from which:

Steel sign rail

Due North

0.84 feet N70°-07-33"E N67°-40'-41"W N17°-43'-54"W

6" Balsam 4" Maple 14.71 feet 26.98 feet 12" Cedar

Signed by Surveyor's Michigan License No.

JOHN R. GARSKE LAND SURVEYOR 1.0. EDLAND

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED JAN., 1983 REVISED OCT., 1995

MAR 0.2 2000

SECTION

SECTION CORNER 30, 29 TABN, RAGW

C-11

