سر	£	~ Up & La	-			
í	· INN	EY & ATION ON THE NTATION OF 1995	•			,
	50, 10	EN				
	-MONO"	_ g**				
	AEIII.	07 1995 ussi ^{ON} land corn		فسيفيث 0	n street	
	APR'			Kegister	B Office ss.	
	E. C.	LAND CORN	ER RECORDATION CE	RTIFICATE Gogebic	County j	Dece
	j = 0	William Filing Requir	rement of Act 74, Mich.	ı. P.A. 1970	Received for recerd t	140
For	corners in	,		2.1	IT HAY OF OCTO	I. K
	Gogebic	Located In:	Corner Code ##	. n 1	994 at 11:15 o'ck	жk
	(County)			A. D.	J.A. A. moordad	ifa
		T 48N R 46W	E-12	<u> </u>	m., and recorded	ral
1.	Public Land Survey	·		Liber	5 OL GORN	
	Section 33	T R			. 154 .	
		Ţ R			one Collins P	eout
_	m O	T R S T R		KINY	Register of B	cods
2.	Property Controlling	S T R			ICES STATES AT IT	
_	in Section					
3.	Miscellaneous	\$ f R		Register of D	eeds Stamp & File Nun	ber
	Property in Sec.	S R				
	Lathia G	Recorded Plat	,			
				A B	CDEFGHIJ	K L
5.	Private Claims				- 5 - 4 3 2	
	1/4 Cor. Comm.	. to Sec's. 32 and	33	3		
	·					
	John P. Goss	, in a field survey onSe	ptember 3, 1994] [
1,	oroby codify that under rec	, in a new survey on	of 1970, the corner points mo	entioned I I		
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the				ed in the	17-16-15-1-17	ı— — <u>[</u> 3-
current manual of survey instructions of the United States Department of the Interior, Bureau of Land					┌─╽╶╂╼╂╌╂╼╂┈╂	
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a						
abo	ve were in conformance will	ith the rules of the Michigan Board re-established, monumented, re-	of Land Surveyors of by a De	ound as	┟╼╁┈┟╶╁╾┼╶┼═┼╌┤	
	ressed below:	re-established, monumented, re-	Indianetica, recovered, it	10	29 28 27 2	25
		corners, all in the same town a	and range may be record	led 11		
NO	TE: Not more than 4 con this certificate.		mu lange, may be record	1231		
	ou filia cei micare.			13		T j
A	Description of original	monument and accessories ar	nd/or subsequent restorat			
۸٠.				÷		
	Original surve	ey by Austin Burt	in 1851. Set Po	st.		
	-					
	Original beari	ing trees.				
	Sugar 12"- 556	50E- 9 links				
	Sugar 6" - N43	3°W- 14 links.		•		
			n. a Osmudania	m na hoina ll	Of feet North	
	On 1928 plans	of Gogebic County	Koad Commissio	u ga being it	34 Teer Moren	
		of Black River Ro				
R		evidence found and/or method	applied in restoring or re-	establishing corner:		
L).	Description of corner e			ald he found d	ue to road	
L).	·					
υ .	No original ex	vdence of the corn	er location cou	ita bo roana a	40 00 roda	
G.	No original en					
G.	No original exconstruction.	ike was found and	has been used o	on plats in Po	wderhorn	Ha.
υ .	No original exconstruction.		has been used o	on plats in Po	wderhorn	Manuel Ma
Δ .	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc	has been used o e line to the W	on plats in Po	wderhorn Wichig	Managara da
6.	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc	has been used o e line to the W	on plats in Po	wderhorn Wichig	
.	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc	has been used o e line to the W	on plats in Po	wderhorn OF MICHIE OF MICHIE JOHN P. GOSS LAND	**************************************
3 .	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc	has been used o e line to the W ounty Register o	on plats in Po	e. * JOHN P. GOSS LAND SURVEYOR	*** # # # # # # # # # # # # # # # # # #
3 .	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc	has been used o e line to the W ounty Register o	on plats in Powers. of Deeds Offic	wderhorn OF MICHIE OF MICHIE JOHN P. GOSS LAND	***
3 .	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc ch on file with Co	has been used on the World Register of the GROUP	on plats in Power of Deeds Offic Approved	e. * JOHN P. GOSS LAND SURVEYOR	***
3.	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc ch on file with Co	has been used on the World Register of the GROUP	on plats in Power of Deeds Offic Approved	e. * JOHN P. GOSS LAND SURVEYOR	*** 10130
5.	No original exconstruction. A railroad spiarea. Corner	ike was found and postion match fenc ch on file with Co	has been used o e line to the W ounty Register o	on plats in Power of Deeds Offic Approved	e. * JOHN P. GOSS LAND SURVEYOR	***
	No original enconstruction. A railroad spiarea. Corner parea.	ike was found and postion match fence ch on file with Co	has been used of the World Register of the World Register of the Register of t	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position	e JOHN P. GOSS LAND SURVEYOR No. 23509	*** * * * **
	No original enconstruction. A railroad spiarea. Corner parea.	ike was found and postion match fence ch on file with Co	has been used of the World Register of the World Register of the Register of t	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position	e JOHN P. GOSS LAND SURVEYOR No. 23509	* * * * HOLLING
	No original enconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research	ike was found and postion match fenc ch on file with Co	has been used of the World Register of the Reg	on plats in Powers of Deeds Offic Approved 10/12/qu e locating the position Epike under the	e JOHN P. GOSS LAND SURVEYOR No. 23509	***
	No original enconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research Description of monume A P.K. Nail many which I estable.	ike was found and postion match fence ch on file with Co Lie ent for corner and accessories arks the corner polished the following	has been used of the World Register of the Register of the Register of the Register of the Registrate	on plats in Power of Deeds Offic Approved 10/12/qu e locating the position of pike under the ects.	e JOHN P. GOSS LAND SURVEYOR No. 23509 of the corner: e nail from	** * * * * * * * * * * * * * * * * * *
	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research Description of monume A P.K. Nail many which I estable.	ike was found and postion match fence ch on file with Co ent for corner and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following control of the corner polished the corner polished the following control of the corner polished the c	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of the under the ects.	e JOHN P. GOSS LAND SURVEYOR No. 23509 of the corner: e nail from	** * * * * * * * * * * * * * * * * * * *
	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research Description of monume A P.K. Nail many which I estable.	ike was found and postion match fence ch on file with Co ent for corner and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following comments #1 and accessories arks the corner polished the following control of the corner polished the corner polished the following control of the corner polished the c	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of the under the ects.	e JOHN P. GOSS LAND SURVEYOR No. 23509 of the corner: e nail from	** * * * * * * * * * * * * * * * * * * *
	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research Description of monume A P.K. Nail many which I estable.	ike was found and postion match fence ch on file with Co Lie ent for corner and accessories arks the corner polished the following	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of the under the ects.	e JOHN P. GOSS LAND SURVEYOR No. 23509 of the corner: e nail from	** * * **
	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research Description of monume A P.K. Nail manume which I established the stable of t	ike was found and postion match fence ch on file with Correct and accessories arks the corner polished the following ce monuments #1 an with 3½" diameter	has been used of a line to the World Register of the GROUP Control of the World Register of the GROUP Control of the World Register of the R	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of pike under the ects. g of 2½" diamed note the cor	of the corner: e nail from ter x 30" long ener postion as	** * * **
	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research Description of monume A P.K. Nail many which I estable I set reference aluminum pipe follows:	ike was found and postion match fence ch on file with Co learn for corner and accessories arks the corner polished the following the monuments #1 and with 3½" diameter 1820E-18	has been used of a line to the World Register of the World Register of the World Register of the World Registron with RR Song bearing objected #2 consisting cap stamped to the Registron with RR Song bearing objected #2 consisting the cap stamped to the Registron Reg	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of pike under the costs. g of 2½" diamed note the cordign post- 1.23	of the corner: e nail from ter x 30" long ner postion as	** * * **
C.	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research aluminum pipe follows: R.M. #1 R.M. #2	ike was found and postion match fence ch on file with Control of the corner and accessories arks the corner polished the following ce monuments #1 and with 3½ diameter \$1.550W-36	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of pike under the costs. g of 2½" diamed note the cordign post- 1.23	of the corner: e nail from ter x 30" long ner postion as	** * * **
C.	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research which I established the stable of t	ike was found and postion match fence ch on file with Control of the corner postion arks the corner postished the following cemonuments #1 and with 3½ diameter \$1.550W-36. P.Pole - N840W-31	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of pike under the costs. g of 2½" diamed note the cordign post- 1.23	of the corner: e nail from ter x 30" long ner postion as	** * * **
C.	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research which I established the stable of t	ike was found and postion match fence ch on file with Control of the corner postion arks the corner postished the following cemonuments #1 and with 3½ diameter \$1.550W-36. P.Pole - N840W-31	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu e locating the position of pike under the costs. g of 2½" diamed note the cordign post- 1.23	of the corner: e nail from ter x 30" long ner postion as	** **
C .	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research which I established I set reference aluminum pipe follows: R.M. #1 R.M. #2 Nail & tag in Nail & tag in Nail & tag in	ike was found and postion match fence ch on file with Co ent for corner and accessories arks the corner polished the following the monuments #1 and with 3½ diameter N620E-48 S550W-36 P.Pole - N840W-31 G.Pole - S500E-43	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu elocating the position Spike under the cts. s of 2½" diamed note the cordign post- 1.23 ign post- 1.13	of the corner: e nail from ter x 30" long ner postion as	** **
C .	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research which I established I set reference aluminum pipe follows: R.M. #1 R.M. #2 Nail & tag in Nail & tag in Nail & tag in	ike was found and postion match fence ch on file with Co ent for corner and accessories arks the corner polished the following the monuments #1 and with 3½ diameter N620E-48 S550W-36 P.Pole - N840W-31 G.Pole - S500E-43	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu elocating the position Spike under the cts. s of 2½" diamed note the cordign post- 1.23 ign post- 1.13	of the corner: e nail from ter x 30" long ner postion as	** **
C.	No original exconstruction. A railroad spiarea. Corner parea. Corner parea. Act 74 research which I established I set reference aluminum pipe follows: R.M. #1 R.M. #2 Nail & tag in Nail & tag in Nail & tag in	ike was found and postion match fence ch on file with Co line with Co line arks the corner polished the following ce monuments #1 and with 3½ diameter N62°E-48 S55°W-36 P.Pole - N84°W-31 G.Pole - S50°E-43	has been used of the World Register of the W	on plats in Polest. of Deeds Offic Approved 10/12/qu elocating the position Spike under the cts. s of 2½" diamed note the cordign post- 1.23 ign post- 1.13	of the corner: e nail from ter x 30" long ner postion as	** **

