

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

GOGEBIC COUNTY

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 50 N. R. 45 W.	A-11, B-11
2. PROPERTY CONTROLLING IN SECTION	T. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. S. R. E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 29, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner A-11: Found 1" I.D. iron pipe reported to have been set by W. S. Bromley, possibly from original bearing tree.

Corner B-11: Found 1" I.D. iron pipe reported to have been set by W. S. Bromley. One old stump fits for original bearing tree.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner A-11: Restored at iron pipe.

Corner B-11: Restored at iron pipe.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner A-11: 1" I.D. x unknown length iron pipe.
 6" W. Birch S65W 19.0 ft., S36, NBT
 4" Sugar N37W 20.6 ft., S25, NBT
 8" Aspen N20E 14.7 ft., S30, NBT

Corner B-11: 1" I.D. x unknown length iron pipe.
 4" Maple S31W 12.1 ft., 1/4S, NBT
 6" Maple S65E 14.9 ft., 1/4S, NBT
 5" Maple N49E 24.8 ft., 1/4S, NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 7-31-80
CHIEF OF SURVEY PARTY
 MICHIGAN REGISTERED LAND SURVEYOR
 Keith L. Sackett
 Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

