SURVEY & REMONUMENTATION

GRATIOT COUNTY REMONUMENTATION PROGRAM LAND CORNER RECORDATION COUNTY

MAY 0 5 1997

RECORDED

Filing Requirement of Act 74, Mich. P.A. 1970

'96 NOV 26 PM 2 33

COMMIS		rinig Kequ	Hement of Act 14, into	11. 1 34. 10.0							
or corners in			00-4-#	ı			\mathcal{C}	١.	ممار س	~	•
<u>Gratiot</u>	Located	i in:	Corner Code #					prod		D.	سر
(County)	Hamilto	on					(/ REGI	STER OF	DEEDS	
I. Public Land Survey	Τ	R <u>1W</u> R R	_A-11								
2. Property Controlling in Section	ST ST	_ R		_	ietor	of De	ands S	amp 8	File N	lumbe	r
3. Miscellaneous	ST_			'''9	istei	01 50	,cus o	will v			
Property in Sec.	sT										
•											
					, Α	В	D 1	E F G	H 1	JK	L M
5. Private Claims					្់្រ	_			_		_,]
					3	6	5	4	3	2	
, William Tingl	e <u>y</u>	a field s	survey on <u>September 1</u>	2, 1996,	4	7 -	8	9	10	11	12
in lines 1 and 2 above we	ere in conformance :	with regulations	P.A. of 1970, the corner points and rules therefore as re	quired in the	5 -	18	17	16	15	14	13
Management or by a decre	e of a Court of Law a	and/or that the o	partment of the Interior, Bure corner points mentioned in lin	es 3, 4 and 5	7		20	21	22	23	24
above were in conformanc Court of Law; establish expressed below:	e with the rules of the ed, re-established,	monumented,	ard of Land Surveyors or by re-monumented, recovered	i, found as	8 9	19	20			2.0	
·	A corners all in ti	he same towr	n and range, may be reco	orded	10	30	29	28	27	26	25
on this certific	ate.		, a.i.a. rango, may we see		12	31	32	33	34	35	36
36-10-2 at Northeast (Post North	N75°E S73°E County Surveyor, Corner witness 50 links	23 links 25 links Liber B, Page	e 105, Records of Minute	s of Survey (s	urve	y of S	ection				
1879 Thomas Harrod, I Corner - stone	Deputy County Su	irvey									
White Oak 34"	N6	88°W 2	5 links								
36 T10N-R2W "T" iron at proporti	er Company, Surv	vey Feelands, Townline. S	0 links Right-of-Way transmiss et "T" iron for Northwes								
North of Section C B. Description of corn Found from in Monume	er evidence found	and/or method	l applied in restoring or re er 25-36, 10-2 (Monume)	establishing co	rner: oortic	on fits	Coun	ty			
Surveyor, Prorate di	stance.										
			s established to perpetuat	e locating the p	ositi	on or t	ne con	ier.			
Set Remonumentation Monument Box	Corner in Monum Sout		25 feet								
Top Center Cable Ris			95 feet								
Top Center Cable Ris Set Nail in Northside	ser Box N45°	°E 59.	85 feet 85 feet								
			etuation of the position	of the original	COM	er					
Signed by Signed by	d as a careful and	Taithful perp	eruation of the position	01 tile original		1996					
Surveyor's Michigan Lic	ense No	30104	1	FORM APPI	ROVETÍ E	Y MICHIO	AN STATE	BOARD OF	LAND SUF	RVEYORS, J	AN. 28, 1971
, .					67/5	& 0510 	17// • • • • • • • • • • • • • • • • • • •	1		REVISED M.	AY 14, 1975 JAN., 1983
ACI GRI . PUB	CEPTED BY THE GR DUP AS THE OFFICI JUIC ACT 345 OF 1990 /	ATIOT COUNTY AL CORNER UN AT A MEETING H	SURVEY PEER IDER MICHIGAN ELD		ž	ALLIN I DAILT Staten Staten	ADB SCAPAL SEA W G'L				-
•		(, t v	-	· .	•	11.)					

William Tingley, PS, Chairman