SEP 0 8 1999

GRATIOT COUNTY REMONUMENTATION PROGRAM

GRATIOT CO. MICH. RECORDED

SECTION

LAND CORNER RECORDATION CERTIFICATE

For comers in Grant Job. Council Council Arcada Township 1. Public Land Survey Sec 6 T.1.1.R. 2.W. 1. R. 1. R			Filin	g Requiren	nent of A	ct 74, N	Mich. P.A. 197	0 .		g ' 95	DEC 2	20	PM 1	. 27
Accade Township 1. Public Land Survey Sec 6			analad la		Corner C	odo#		,	1. 1.		`		·	
Public Land Survey 1. Public Land Survey 1. Public Land Survey 1. R. T. T. R. T. R. T. R. T. R. T. R. T. R. T. T. R. T. T. R. T. T. R. T.		L	ocateo in:		Comer C	oue #		ر در موار دو	ge ^e l s	:	Jane	文伽	Œ.,	ىمى
1. Public Land Survey Sec 6 T. 1.1 R. 2.W. As3.5cc.Coznex T. R. T. R. T.	•		Arcada Towr	nship			tgut I rults	1	4 - 1		REC	ister o	F DEEDS	ı
2. Property Controlling S T R R in Section S T R R in Section S T R R in Section S T R R 4. Lot No. Recorded Plat 5. Private Claims 6. Recorded Plat 6. Private Claims 7. R 7. R 7. R 7. R 7. R 8. R 8. Register of Deeds Stamp & File Number 8. Property in Sec. S T R 4. Lot No. Recorded Plat 7. R 8. R 8. Register of Deeds Stamp & File Number 8. Register of Deeds Stamp & File Number 9. Recorded Plat 9. R	1. Public Land Survey	Sec 6 T	11 NR 2	W_	A-3,Se	c Corne	er 🔭							
2. Property Controlling S T R R in Section S T R Property in Sec. S T R Property in Sec. S T R Property in Sec. S T R 4. Lot No. Recorded Plat 5. Private Calms 6. No. Recorded Plat 6. Private Calms 7. No. Recorded Plat 8. No. Recorded P														
2. Property Controlling S_T_R_ In Section S_T_R_ Miscollaneous S_T_R_ 4. Lot No. Recorded Plat 5. Private Claims 4. Lot No. Recorded Plat 6. Private Claims 6. Private Claims 6. Private Claims 6. Private Claims 7. R_ 8. Register of Deads Stamp & File Number 8. Miscollaneous S_T_R_ 9. Private Claims 9. Register of Deads Stamp & File Number 9. Register							-							
in Section S T R Property in Sec. S T R 4. Lot No. Recorded Plat 5. Private Claims 7. Private Claims 8. T R 4. Lot No. Recorded Plat 1. William Tingley a field survey on September 22, 1995 4. T 8 9 C D F F 6 H I J K I M 2 6 5 5 4 3 2 2 1 3 6 5 5 4 3 2 2 1 3 7 8 9 7 10 11 12 4 7 8 9 7 10 11 12 4 7 8 9 7 10 11 12 4 7 8 9 7 10 11 12 4 7 8 9 7 10 11 12 5 10 15 14 13 5 15 14 14 5 15 14 14 5 15 14 14 5 15 14 14 5 15 14 14 5 15 14 14 5 15 14 14 5 15 14 14 5	2. Property Controlling				•		- i							
3. Miscollaneous S T R Property in Sec. S T R 4. Lot No. Recorded Plat 5. Private Claims 6. Private Claims 7. Private Claims 7. William Tingley a field survey on September 20, 1995 8. Private Claims 8. T R 9. Private Claims 8. T R 9. Private Claims 9. Private Clai	• •						- 1		- 4 D			o mu a l	\] 	_
Property in Sec. S. T. R. 4. Lot No. Recorded Plat	3. Miscellaneous						K	egiste	r ot De	eeas >	tamp a	k riie i	aumpe	r
5. Private Claims 2	Property in Sec.	ST	R	- 			-				·			
5. Private Claims 1. Killiam Tiagley a field survey on September 20, 1935 4 7 8 9 9 10 111 12 6 hereby certify that under requirements of PA. 74. Michigan PA of 1970, the corner points mentioned in fines 1 and 2 above were in conformance with equilations and rules benefore as required in the fine in fines 1 and 2 above were in conformance with subset bepartment of the letterior Buseus of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in fines 3, 4 and 5 8 above were in conformance with the rules of the Michigan Board of Land Surveyor or by a Decree of a Court of Law and/or that the corner points mentioned in fines 3, 4 and 5 8 above were in conformance with the rules of the Michigan Board of Land Surveyor or by a Decree of a Court of Law established, monumented, re-monumented, recovered, found as recommended, re-established, monumented, re-monumented, recovered, found as compared below on this certificate. NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: 1822, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beech 11" \$64/E 48 links Beech 18" NAT'E 24 links 1886, D. Altenburg, County Surveyor, Record of Minutes of Survey, Liber C, Page 149 in County Drain Office Long Stone and Stones Elim 6" \$32,3/4" 78 Binks 1986, Michigan State Highway Department, Resurfacing using 1931 construction plans. Station 237 +74.3 Emerson Corner, Station 237 +88.9 Arroad Corner Station 237 +88.9 Arroad Corner Stone (Emerson Corner) Corner fance post Southwest 39.25 feet PSTO, M. Hunter, Surveyor, Survey RO-303 Northwest Corner fance post Southwest 31.25 feet PSTO, M. Hunter, Surveyor, Survey RO-303 Northwest Corner fance post Southwest 31.25 feet Northwest Corner fance post Southwest 51.2 Corner (no bearing trees) 1777, D. Whitein Thylley, PS, Chalama William Thyley, PS, Chal								۵	RI	c n	F F (э. н	t .i k	I M
co heraby certify that ender requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or ya decree of a Count of Law and the state of the Michigan Board of Land Surveyins mentioned in lines 3, 4 and 5	5. Private Claims							۱'		<u> </u>			T	
i. William Tingley a field survey on September 20, 1395 the storty certify that notes requirements of P.A. 74. Michigan P.A. of 1070, the conce points mentioned in the stort of the stort								i		5	4	3	2)
to hereby certify that under requirements of PA. 74, Michigan PA. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and nuise therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and first that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a court of Law, cestablished, re-established, monumented, re-monumented, recovered, found a sexpressed below. NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: 1852, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beech 11* 364-TE 48 links 1886, D. Altenburg, County Surveyor, Record of Minutes of Survey, Liber C, Page 149 in County Drain Office 1.0ng Stone and Stones 18	I,William_Tingle	ξΥ		_ a field surve	y on	Septemb	er 20. 1995	4		8	9	10	11	12
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of oursey instructions of the United States Department of the Interior, Bureau of Land Management of to grow point in conformance with the rules of the Michigan Board of Land Surveyors by a Decree of a Court of Law and/or that the corner points meritained in lines 3, 4 and 5 and 3								i	18	-17	16	-15	14	1.2
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, monumented, re-monumented, recovered, found as a corpessed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: 1852, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beech 14" 864°E 48 links Beech 18" N47°E 24 links 1888, D. Altenburg, County Surveyor, Record of Minutes of Survey, Liber C, Page 149 in County Drain Office Long Stone and Stones Elm 6" \$32-34°W 78 links Sugar 4" N55-1/4" \$5-1/4 links Sugar 4" N55-1/4" \$5-1/4 links 1981, Michigan Stell Highway Department, Resurfacing using 1931 construction plans. Station 237 +74.3 Emerson Corner, Stone (Emerson Corner) Corner fence post Southwest 39.25 feet Public #10070, Survey #G-528 Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) 1977, D. Whither #10070, Survey Liber 400, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" Iron Bar in Monument Box 1977, D. Whither #10070, Survey Liber 400, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" Iron Bar in Monument Box 1977, D. Whither #20070, Survey Liber 400, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" Iron Bar in Monument Box 1977, D. Whither #20070, Survey Liber 400, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" Iron Bar in Monument Box 1977, D. Whither #20070, Survey Liber 400, Page 256 Monument Box 5/4 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Conterline Monument Box Suthwest 61.4 feet Centerline Monument Box Suthwest 51.4 feet Centerline Monument Box Suthwest 51.5 feet South	current manual of survey in	structions of	the United St	tates Departm	ent of the	Interior, B	ureau of Land	ſ						13
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. **NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. **A Description of original monument and accessories and/or subsequent restoration: **1852, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beach 11" **Seech 18" **NA7'E 24 links** **Besch 18" **N47'E 24 links** **Besch 18" **N47'E 24 links** **Besch 18" **N47'E 24 links** **Sugar 6" **S32:3/4"W **78 links** **Sugar 6" **S95-3/4"E 78 links* **S96-3/4"E 78 links* **Sugar 6" **S95-3/4"E 78 links* **Sugar 6" **S95-3/4"E 78 links* **Sugar 6" **S95-3/4"E 78 links* **S95-3/4"E 78 links* **Sugar 6" **S95-3/4"E 78 links* **S95-3/4"E 78 links* **S95-3/4"E 78 links* **Sugar 6" **S95-3/4"E 78 links* **S95-3/4"E 78 links* **S96-3/4"E 67 links* **S96-3/4"E 6								1	19 -	20	21	- 22	23	- 24
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration: 1852, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beech 11" S64"E 46 links Beech 11" S44"E 24 links Beech 11" S44"E 24 links Beech 11" S44"E 74 links Beech 11" S45"E 74 links Beech 11" S45"E 74 links Sugar 4" N85-1/4" 59-1/4 links Sugar 4" N85-1/4" 59-1/4 links Sugar 4" S52-3/4"E 78 links Sugar 6" S52-3/4"E 78 links S184in 23" + 86.9 Arcada Corner Stone (Emerson Corner) Corner fence post Northwest 39.25 feet Corner fence post Northwest 31.25 feet S70, M. Hunter, Surveyor, Survey #G-625 Shows Monument Box 5-4 feet North of 11-3 Corner (no bearing trees) S71, Weilter #10070, Survey Liber 408, Page 237 Shows Monument Box 5-6 feet North of 11-3 Corner (no bearing trees) S72, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box Nying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southwest 61.4 feet Centerline Monument Box South 5.3 feet Conterline Monument Box Southwest 61.4 feet Centerline Cable Box Nying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southwest 61.4 feet Centerline Cable Box Nying 5.3 feet North of Southwest 61.4 feet Centerline Cable Box Nying 5.3 feet North of Southwest 61.4 feet Centerline Cable Box Nying 5.3 feet North of Southwest 61.4 feet Centerline Cable Box Nying 5.3 feet North of Southwest 61.4 feet Centerline Cable Box Nying 5.3 feet North of Southwest 61.4 feet Centerline		d, re-establ	ished, monu	mented, re-m	nonumented	recover	red, found as	· I	30	29	28	27	26	25
A. Description of original monument and accessories and/or subsequent restoration: 1825, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beech 14" S64"E 48 links Beech 18" N47"E 24 links 1888, D. Altenburg, County Surveyor, Record of Minutes of Survey, Liber C, Page 149 in County Drain Office Long Stone and Stones Elm 6" \$32-314"W 78 links Sugar 6" \$85-314"E 78 links Sugar 6" \$85-34"E 69 links Suga	NOTE: Not more than 4	4 corners. a	ll in the sar	ne town and	l range. m	av be re	corded	- 1						
A Description of original monument and accessories and/or subsequent restoration: 1852, Austin Burt, Deputy Surveyor, GLO Notes, Resurvey of Township Intersected West boundary 10 links North of old Corner Beech 11" S64"E 48 links Beech 18" N47"E 24 links 1888, D. Altenburg, County Surveyor, Record of Minutes of Survey, Liber C, Page 149 in County Drain Office Long Stone and Stones Elm 6" S32-3/4" 78 links Sugar 4" N55-1/4" 59-1/4 links Sugar 4" N55-1/4" 59-1/4 links Sugar 6" S32-3/4" 78 links 1961, Michigan State 19/4 may Department, Resurfacing using 1931 construction plans. Station 237 +74.3 Emerson Corner, Station 237 +88.9 Arcada Corner Stone (Emerson Corner) Corner fence post Northwest 39.25 feet PUBLIC ACT 345 OF 1999 AT AMEETING HELD 11-29-75 Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) 1977, D. Whittier #1070, Survey Liber 498, Page 237 Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) Will an Tingley, PS, Chairman 1987, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southwest 61.4 feet Centerline Monument Box South 5.3 feet Conditioned on back B. Description of corner evidence found and/or method applied in restoring or reestabilishing corner. Found 38" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Continued on back B. Description of corner evidence found and/or method applied in restoring or reestabilishing corner. Contentrine Cable Box Ma5" 58.9 feet Contentrine Cable Box Ma5" 58.9 feet Contentrine Cable Box Ma5" 58.9 feet Contentrine Corner Concrete Gutter N70"E 67.92 feet Southwest Corner Concrete Gutter N70"E 67.92 feet Corner of 1-12-3 South 54.4 feet This corner is accepted as a careful and faithful reestabilishment of the original corner.						,		- 1	-31	32	-33	34	35	36
Stone (Emerson Corner) Corner fence post Corner fence post Northwest 31.25 feet 1970, M. Hunter, Surveyor, Survey #G-626 Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) 1977, D. Whittier #10070, Survey Liber 408, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" iron Bar in Monument Box 15.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southwest Southw	1888, D. Altenburg, Cou Long Stone and Stone Elm 6" S: Sugar 4" N Sugar 6" S 1961, Michigan State Hi	inty Survey 32-3/4°W 55-1/4° 65-3/4°E ghway Dep	78 links 59-1/4 li 78 links	nks			ction plans. S	tation	237 +	74.3 E	mersoi			.550
Corner fence post Corner fence post Corner fence post Corner fence post Northwest S1.25 feet 1970, M. Hunter, Surveyor, Survey #G-626 Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) 1977, D. Whittier #10070, Survey Liber 408, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" iron Bar in Monument Box 1982, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southeast Southwest Southwest S1.4 feet Centerline Monument Box Continued on back Continued on back B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45"W S8.69 feet Centerline North Telephone Box S45"W S8.69 feet Southwest Corner Concrete Gutter S30"E G1.45 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by Date 12 72 1995							ACCEP	TED BY	THE	GRATIO	T COUN	UNDER	RVEY F	GAN
Corner fence post Northwest 31.25 feet 1970, M. Hunter, Surveyor, Survey #G-626 Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) William Tingley, PS, Chairman 1977, D. Whittier #10070, Survey Liber 408, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" iron Bar in Monument Box 1982, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southeast 68.9 feet Spike in 24" Maple Southwest 61.4 feet Centerline Monument Box South 5.3 feet Continued on back Continued on back Continued on back Continued on back 10" Continue	Corner fence post Southwest 39.25 feet							ACT 34	5 OF 19	90 AT A	MEETIN	G HELD	11.20	7.95
Shows Monument Box 5.4 feet North of 11-3 Corner (no bearing trees) 1977, D. Whittier #10070, Survey Liber 408, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" Iron Bar in Monument Box 1982, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southeast 68.9 feet Spike in 14" Maple Southwest 61.4 feet Centerline Monument Box South 5.3 feet Continued on back Corner evidence found and/or method applied in restoring or reestablishing corner: Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45" 58.69 feet Centerline Cable Box N45" 58.69 feet Centerline North Telephone Box S45"W 60.44 feet Southeast Corner Concrete Gutter N70"E 67.92 feet Southwest Corner Concrete Gutter S35"E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by Date 12-1-1995				31.25 feet		-								
1977, D. Whittier #10070, Survey Liber 408, Page 237 Shows Northwest Corner, Section 7 at a distance of 2641.05 feet North of West 1/4 corner, a 3/4" iron Bar in Monument Box 1982, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southeast 68.9 feet Spike in 24" Maple Southwest 61.4 feet Centerline Monument Box Continued on back NO 30104 Continued on back Continued on back Contentine North-South pavement Contentine North-South pavement Contentine North Telephone Box at Centerline pavement East and Centerline North-South pavement Contentine Cable Box N45'W Southeast Corner Concrete Gutter N70°E Southeast Corner Concrete Gutter N70°E Southwest Corner Concrete Gutter N70°E South Sou										Willia	n Tinaley	, PS. CI	nairman	
1982, T. Mueller #25861, LCRC, Liber 2, Page 46 Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southeast 68.9 feet Spike in 24" Maple Southwest 61.4 feet Centerline Monument Box South 5.3 feet Continued on back Contending former: Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45*W S8.69 feet Centerline North Telephone Box S45*W 60.44 feet Southwest Corner Concrete Gutter S35°E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by Date C 7 2 1995'	1977, D. Whittier #10070), Survey Li	ber 408, Pa	ge 237										
Monument Box lying 5.3 feet North of Southeast Corner section 1, 11-3 Used center of box, could not open Spike in 14" Maple Southeast 68.9 feet Spike in 24" Maple Southwest 61.4 feet Centerline Monument Box South 5.3 feet Continued on back					1.05 feet N	lorth of \	West 1/4 corne	r, a 3/	4" Iro	n Bari	n Mon	ument	Box	٠,
Used center of box, could not open Spike in 14" Maple Southeast 68.9 feet Spike in 24" Maple Southwest 61.4 feet Centerline Monument Box South Continued on back Co					section 1.	11-3				2		i.	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	
Spike in 24" Maple Centerline Monument Box South	Used center of box, o					, •					13,	VILLIA	M G.	y
Continued on back B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45"W 58.69 feet Centerline North Telephone Box S45"W 60.44 feet Southeast Corner Concrete Gutter N70"E 67.92 feet Southwest Corner Concrete Gutter Signed by Date 12" Pipe and 3/8" rod in Monument Box Centerline North Telephone Box 58.69 feet Conterline North Telephone Box 58.69 feet Southeast Corner Concrete Gutter Signed by Date 12" Pipe and 3/8" rod in Monument Box Centerline North South pavement Signed by Date 14" Pipe in Monument Box Corner of 1-12-3 South Date 15" Pipe and 3/8" rod in Monument Box Centerline North-South pavement Corner of the position of the original corner. Signed by Date 15" Pipe and 3/8" rod in Monument Box Corner of 1-12-3 South 5.4 feet		_			-									t ar
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner. Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45"W 58.69 feet Centerline North Telephone Box S45"W 60.44 feet Southeast Corner Concrete Gutter N70"E 67.92 feet Southwest Corner Concrete Gutter S35"E 61.55 feet Corner of 1-12-3 South This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by Date 12-72-1995										1. A. B.		SURVE	YOR	<u>C</u> .
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45"W 58.69 feet Centerline North Telephone Box S45"W 60.44 feet Southeast Corner Concrete Gutter N70"E 67.92 feet Southwest Corner Concrete Gutter S35"E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by Date 12-72-, 1995'	ocincinno monantin	I DOX SI	buui	0.0 16	GL					in the			-	Q. 1
Found 3/8" Rod raised with 1/2" Pipe in Monument Box at Centerline pavement East and Centerline North-South pavement C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45°W 58.69 feet Centerline North Telephone Box S45°W 60.44 feet Southeast Corner Concrete Gutter N70°E 67.92 feet Southwest Corner Concrete Gutter S35°E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by Date 12-72-, 1995'	·	·									TO No. PA	0.000	MAL	50.8
Set Remonumentation Monument over 1/2" Pipe and 3/8" rod in Monument Box Centerline Cable Box N45*W 58.69 feet Centerline North Telephone Box S45*W 60.44 feet Southeast Corner Concrete Gutter N70°E 67.92 feet Southwest Corner Concrete Gutter S35°E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by 1.	Found 3/8" Rod raised v	vith 1/2" Pip	e in Monur	nent Box at	Centerline	e pavem	ent East and C	enteri	ine No	orth-Sc	outh pa	Myene Sveme	nt	•
Centerline North Telephone Box S45°W 60.44 feet Southeast Corner Concrete Gutter N70°E 67.92 feet Southwest Corner Concrete Gutter S35°E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by 1. Date 12-72, 1995	Set Remonumentation &	THE REAL PROPERTY.	ver 1/2" Pi	pe and 3/8"	rod in Mor	perperer	ate iocating the	positio	on of ti	he corr	er:			
Southeast Corner Concrete Gutter N70°E 67.92 feet Southwest Corner Concrete Gutter S35°E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by 1. Date 12-72, 1995'		ibona Par												
Southwest Corner Concrete Gutter S35°E 61.55 feet Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by 1. Date 12-72, 1995'														
Corner of 1-12-3 South 5.4 feet This corner is accepted as a careful and faithful reestablishment of the position of the original corner. Signed by 1.														
Signed by Williams No. 272, 1995		-												
Signed by Williams No. 272, 1995	This comerie accented	20 2 02505-	l and falshfi	ul rocatabii-	hmant -f	tha neet	tion of the ent-	ilmal -						
Company of Michigan License Ma	1 \ \ \ \	as a carefu		Cara Ca	ranche of	-	am'	_		•				
		nse No.	30104		7					AN STATE	OARD OF	AND #1104	/FYORR 14	N. 21 4074

LI8ER

NV 2. 9 K J. 1

Continued from front (A-3, 11-2)

1987, W. Ruddell #14769, Survey, Liber 474, Page 414

Found Monument Box

Nail and Cap in 24" Apple Nail and Cap in 9" Maple Nail and Cap in 26" Maple

Northeast Southeast 57.35 feet

CONTRACTOR COURTE RENKER

Marie Co

Southwest

69.15 feet

Locates 1/4 1/4 corner at 1320.55 feet South (Set "T" Iron 33 feet East)

69.90 feet

1987, W. Ruddell #14769, LCRC, Liber 2, Page 92

Same data as above except 24" Apple is a 24" Maple

SURVEY & REMONUMENTATION

SEP 0 8 1999

SECTION

LI8ER

en in rappen in a comment of the second to the comment than the second to the