

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Grand Traverse Co. Located In _____ Corner Code # _____
 (County)

- | | | | | | |
|--------------------------------------|-------------|--------------|--------------|--|----------|
| 1. Public Land Survey | T _____ | R _____ | | | |
| | T _____ | R _____ | | | |
| 2. Property Controlling in Section | S <u>34</u> | T <u>25N</u> | R <u>11W</u> | | <u>8</u> |
| | S _____ | T _____ | R _____ | | |
| 3. Miscellaneous Property in Section | S _____ | T _____ | R _____ | | |
| | S _____ | T _____ | R _____ | | |

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on July 22, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:
8 - None

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
8 - CW 1/16 Section 34, T25N, R11W - Set stamped 2" Aluminum cap on 5/8" x 34" rebar per standard BLM procedure. Cor. of fence posts W & S is 2.5' W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
8 - 2" Aluminum Cap stamped "CW 1/16 S34"
 N03°W 63.88' to set N & T in E. side 6" Poplar
 S17°W 9.30' to set N & T in E. side 4" x 6" fence post
 S83°W 2.95' to set N & T in N. side 4" x 6" fence post
 N64°W 26.40' to set N & T in NE side 5" Tamarack
 Set Blue Carsonite Post 1' East.



Signed by: Craig W. McVean
 Surveyor's Michigan License No.: 39088

Date: 10/25/2004