LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED	IN:	CORN	ER CODE NUMB	ER		
	1. PUBLIC LAND SURVEY	T25	N. R. <u>11</u>	₩. <u>E-10</u>	; G-9			
	2. PROPERTY CONTROLL- 28	,T. <u>25</u>	N. C, R. <u>11</u>	Q . 8; 1	1; 12			
	3. MISCELLANEOUS PROPERTY IN SECTION	,T	N. S., R	E.				
	4. LOT NO, RECORDED PLAT							
	5. PRIVATE CLAIMS		-	<u></u>	<u> </u>		F DEEDS STAMP	AND
	I, Carl F. Roser do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on April 1, 19.74, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:							
	SAKKIK NYAKKAKKAKA KAKAKIK KA	XXXXXXX YASYIYA	······································	(XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	(XXXXXXXXXXX	XXXX		
	C. (CONTINUED)	WINNEY AND AN	CCG S BULFED '	Shieth Civil Carl	12			
	11			Set 1"x3	6" pipe, bu	uried in N-S		
	Set 1"x72" pipe & c	edar post		dirt r		0105 05 06		
	w/location tag	02.71		34" W. P 7" S. P		81 ⁰ E 95.06 80 ⁰ W 29.50		
	0 00001	92.7' 103.8			Maple Si	22°W 52.92		
	4" Cedar N73 ⁰ W	103.0			-S dirt roa			
					r post w/lo			
						Due W 33'		
	B. Description of corner evid				restoring or re	-establishing corn	er:	
- 10	Reestablish corner							
-9	Recovered cedar sta Record (1908).	ke and U.S	S.B.T. (st	tump) SW j	per E. P. W	laterman Surve	y of	
8	Established corner	per standa	ard B.L.M	. instruc	tions.			
11	Established corner							
12	Established corner per standard B.L.M. instructions.							
	C. Description of monument	for corner an	d accessori	es establish	ed to perpetua	te locating the po	sition of the c	orner:
	E-10			6-9			8	
Set	DNR mon. & cedar post	•	Found	stake, ad	ded DNR mor	ı. & 1"x5' p	ipe & cedaration tag	r post
10-1	2" Quad. B. Cherry Due	N 3.5'	ceda	r post	770 _E 17	w/100 2.1 12" Ced	ar N770N	39.2
10''	B. Cherry S49 ^o k B. Cherry N34 ^o E	66.6'	12" Ce 11" Ce	dar S dar S	73 E 14 74 ⁰ W 15	5.5 6" Ced	ar NO10W	21.7
	B. Cherry N34 ^O E Road Due E		15" Ce	dar N	73 ⁰ E 12 74 ⁰ W 15 44 ⁰ W 26	5.5 6" Ced 5.6 7" Map	le SOS ^O E	30.7
., 0								
		_						
	$\bigcap \bigcap \mathcal{F}$	Danel	<u>`</u>		DATE _	7-3-74		
	SIGNED BY Carl 7. Roser				DATE _			
	SURVEYOR'S MICHIGAN RE	EGISTRATION	NO	12028		THE OF MICK	AL)	
	FOR STATE AND UNITED STATES AGENCIES:				: S	CARL F. ROSER		
	SIGNED BY	CHIEF OF S	URVEY PARTY		DATE	LAND SURVEYOR	* <u>* </u>	
	APPROVED AND SIGNED BY	.,		EB 1 44.6 0		No. 12028	<u> </u>	
	the same elected b	- MIC	HIGAN REGISTER	ED LAND SURVEY	vn e	THEO LAND SUYSE	λL)	
						MAYFIELD	1WP.	

E-10

G-9

12" N-S

SURVEYOR'S MICHIGAN REGISTRATION NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 26, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND CONTROL OF STATE OF STATE